

LJMU Research Online

Tso, FP, Jouet, S and Pezaros, DP

Network and Server Resource Management Strategies for Data Centre Infrastructures: A Survey

http://researchonline.ljmu.ac.uk/id/eprint/3853/

Article

Citation (please note it is advisable to refer to the publisher's version if you intend to cite from this work)

Tso, FP, Jouet, S and Pezaros, DP (2016) Network and Server Resource Management Strategies for Data Centre Infrastructures: A Survey. Computer Networks. ISSN 1389-1286

LJMU has developed LJMU Research Online for users to access the research output of the University more effectively. Copyright © and Moral Rights for the papers on this site are retained by the individual authors and/or other copyright owners. Users may download and/or print one copy of any article(s) in LJMU Research Online to facilitate their private study or for non-commercial research. You may not engage in further distribution of the material or use it for any profit-making activities or any commercial gain.

The version presented here may differ from the published version or from the version of the record. Please see the repository URL above for details on accessing the published version and note that access may require a subscription.

For more information please contact researchonline@ljmu.ac.uk

http://researchonline.ljmu.ac.uk/

Network and Server Resource Management Strategies for Data Centre Infrastructures: A Survey

Fung Po Tso^{a,*}, Simon Jouet^b, Dimitrios P. Pezaros^b

^aDepartment of Computer Science, Liverpool John Moores University, L3 3AF, UK ^bSchool of Computing Science, University of Glasgow, G12 8RZ, UK

Abstract

The advent of virtualisation and the increasing demand for outsourced, elastic compute charged on a pay-as-you-use basis has stimulated the development of large-scale Cloud Data Centres (DCs) housing tens of thousands of computer clusters. Of the significant capital outlay required for building and operating such infrastructures, server and network equipment account for 45% and 15% of the total cost, respectively, making resource utilisation efficiency paramount in order to increase the operators' Return-on-Investment (RoI).

In this paper, we present an extensive survey on the management of server and network resources over virtualised Cloud DC infrastructures, highlighting key concepts and results, and critically discussing their limitations and implications for future research opportunities. We highlight the need for and benefits of adaptive resource provisioning that alleviates reliance on static utilisation prediction models and exploits direct measurement of resource utilisation on servers and network nodes. Coupling such distributed measurement with logically-centralised Software Defined Networking (SDN) principles, we subsequently discuss the challenges and opportunities for converged resource management over converged ICT environments, through unifying control loops to globally orchestrate adaptive and load-sensitive resource provisioning. *Keywords:* Cloud Data Centre, Virtualisation Management, Network

Preprint submitted to Journal of Computer Networks

^{*}Corresponding author

Email address: p.tso@ljmu.ac.uk (Fung Po Tso)

1. Introduction

Cloud computing is an important IT paradigm where enterprises outsource ICT infrastructure and resources based on a *pay-as-you-use* service model. This model relieves enterprises from significant capital expenditure (CAPEX) costs ⁵ for purchasing and maintaining in-house permanent hardware and software assets. Instead, they use operating expense budgets (OPEX) to fund their ICT infrastructure and eliminate maintenance expenses, allowing them to focus on core business innovation. One of the most immediate benefits of using Cloud services is the ability to increase infrastructural capacity swiftly and at lower costs, therefore being able to adapt to changes in the market without complex

procurement processes, and respond flexibly to unexpected demand. Recent years have witnessed a significant growth in the adoption of Cloud Computing. The public Cloud computing market has expanded by 14% in 2015 to total US\$175 billion, according to Gartner Inc. [1], whilst total spending worldwide is anticipated to continue flourishing at a Compound Annual Growth Rate

(CAGR) of 17.7% until 2016 [2].

Underpinning Cloud Computing are virtualised infrastructures hosted over Data Centres (DCs) which are in turn maintained and managed at scale by national or global operators, such as Amazon, Rackspace, Microsoft, and Google.

- These implement different variations of the *-as-a-Service (*aaS) paradigm, including Infrastructure-as-a-Service (IaaS, e.g., Amazon's EC2 and Google's Compute Engine), Platform-as-a-Service (PaaS, e.g., Microsoft's Azure and Rackspace's Cloud Sites) and Software-as-a-Service (SaaS, e.g., Facebook and Google Docs).
- It was anecdotally reported that the number of servers owned by some major Cloud service providers and operators could be more than a million [3]. They are hosted in Cloud DCs, each typically housing tens of thousands of servers [4]. In order to be sustainable, the significant capital outlay required for building

a DC makes maximisation of Return on Investment (RoI) crucial, which in turn necessitates efficient and adaptive resource usage of the virtualised physical infrastructure [5][6][7]. With the advent of virtualisation and multi-tenancy, computing resources are shared amongst multiple tenants, preventing hard re-

source commitment and therefore servers from being idle. However, this soft resource allocation results in significant load fluctuation in short timescales due

³⁵ to the ebb and flow of user demand.

30

DC infrastructures are therefore vulnerable to performance degradation from factors such as network congestion and contention on shared resources. Managing such dynamism in short timescales is particularly challenging. Many Cloud applications such as, Hadoop running over Cloud DCs exploit a fine-grained

- ⁴⁰ hierarchical task decomposition into stages, each of which can involve multiple instances running in parallel on different physical hosts and communicating between them. In some intermediate stages, computation results yielded from subtasks are gathered on to fewer number of servers to produce input for subsequent and final compute stages. In this partition/aggregate work pattern, it is
- essential for all subtasks to complete in time in order for a job to complete since any failed subtask will have to be re-executed and keep others "waiting" for it to complete. As a result, the completion time of each single subtask ultimately determines the overall job completion time. This is wasteful both for CPU cycles and network bandwidth, and can have a knock-on effect on the response time of different services and different tenants.

Consequently, DC resource management has become a complex problem due to the inability to gather accurate infrastructure-wide resource usage information in short timescales and in turn to forecast resource availability. Recent research has revealed that DC workload patterns at coarse time-scales (i.e.,

⁵⁵ hours) exhibit weekend/weekday variations [8], but at finer-grained timescales, the workload patterns are bursty and unpredictable [6][9][10]. The measurement results indicate that in order to adapt to transient load fluctuation, a fine-grained temporal and spatial approach is needed. For fine temporal granularity, control loops are needed to obtain levels of resource utilisation in short timescales for better characterising workload patterns. For spatial granularity, individual flows size, server availability, network link utilisation, etc., need to be measured and used as additional input to resource provisioning algorithms [10].

Currently, to cope with performance variability and unpredictability, DCs are engineered to tolerate a certain degree of demand fluctuation by over-

⁶⁵ provisioning, or by holding certain resources as a reserve [11][12]. However, over-provisioning within Cloud DCs is expensive [4]. Alternatively, adaptive provisioning policies can be implemented to ensure that Cloud providers adhere to their Service Level Agreements (SLAs) while maximising the utilisation of the underlying infrastructure.

- ⁷⁰ Cloud resource management requires complex instrumentation mechanisms and algorithms for multi-objective optimisation to measure and account for e.g., server, network, and power usage efficiency. In this paper, we provide a critical survey of resource management strategies for virtualised Data Centre infrastructures. We focus on two key infrastructural aspects: the servers and
- ⁷⁵ the underlying network. These two pillars not only represent the most costly infrastructural elements, up to 60% of the cost of a data centre [4], that need to be managed and provisioned in an efficient and effective manner, they also adequately capture the level of granularity of resource contention and multiplexing over Cloud DCs [13]. In virtualised DCs, virtual Machines (VMs) are the
- ⁸⁰ fundamental entities used by users over both public and private infrastructure Clouds while traffic is multiplexed and controlled at the level of individual flows over the DC network. We discuss management strategies for the static and dynamic allocation of virtual resources over physical servers to improve response times, power and energy consumption, and network bandwidth utilisation. We
- present the network-wide characteristics of typical DC workloads, and we review the most prominent work on traffic engineering strategies to achieve different network-wide objectives. In addition, we discuss developments on traffic flow admission and congestion control for Cloud DCs that primarily seek to harness the underlying redundancy in network bandwidth to maximise intra-DC pair-
- ⁹⁰ wise application throughput. In each of these areas, we highlight the limitations

of the state-of-the-art and we discuss efforts towards more adaptive and more dynamic, closed-loop resource management and control.

The remainder of this paper is structured as follows: Section 2 presents the dominant DC network architectures and management topologies used to leverage network and server resource redundancy and enable horizontal (rather than vertical) infrastructure expansion. We then critically discuss the most important and influential developments on server, network, and flow control management over Cloud DCs, in sections 3, 4 and 5, respectively. Within each category, we present the main optimisation objectives and main techniques for achieving

them. We identify areas for future development and open research issues that are yet to be addressed. In Section 6, we raise the issue of the current disjoint management and control of diverse physical and virtual resources in the DC, and we discuss the inefficiencies this lack of synergy between control mechanisms can lead to. We then describe research challenges and opportunities for converged control and resource management for virtualised Cloud DCs. Finally,

Section 7 concludes the paper.

2. Data Centre Topologies

In this section, we provide a critical review of the dominant Cloud Data Centre (DC) network architectures, outlining their operational characteristics, limitations and expansion strategies.

2.1. Conventional DC Architecture

Conventional DC architectures are built on tree-like hierarchy with highdensity, high-cost hardware [14], as depicted in Fig. 1a. The network is a tree containing a layer of servers arranged in racks at the bottom. Each server rack typically hosts 20-40 servers connected to a Top of Rack (ToR) switch with a 1Gb/s link. Each ToR switch connects to two aggregation switches for redundancy. For the same reason, aggregation switches connect to core switches/routers that manage traffic in and out of the DC. The hierarchical



Figure 1: Switch-centric ((a) & (b)) and server-centric ((c) & (d)) Cloud data centre topologies.

- configuration of the network topology means that traffic destined to servers ¹²⁰ in different racks must go through the aggregation or the core switches of the network. Therefore, aggregation switches usually have larger buffers as well as higher throughput and port density, and are significantly more expensive than ToR switches. To make the network fabric cost-effective, higher layer links are typically oversubscribed by factors of 10:1 to 80:1, limiting the bandwidth
- between servers in different branches [4]. Links in the same rack are not oversubscribed and thus collocated servers can operate at full link rate. Cross-rack communication is routed through the higher layers of the topology and therefore, in case of persistent and high-load communication between racks, the aggregation and core switches can become congested and result in high latency and
- packet loss. To increase capacity, network operators must resolve to vertical expansion, in which operators replace overloaded switches with higher-cost, higher capacity ones [15].

2.2. Clos/Fat-tree Architecture

Modern data centre architectures [16][17][6] have been proposed to reduce or even remove oversubscription altogether. Representative work, such as e.g., Clos-Tree [6] and Fat-Tree [16], promote horizontal rather than the traditional vertical expansion. Instead of replacing higher-layer costly switches, network operators can add inexpensive commodity switches to expand their network horizontally using a fat-tree topology (Clos topology for VL2). Dense intercon-

- nect in these new fabrics provides a larger number of redundant paths between any given source and destination edge switch (i.e. rich equal cost path redundancy in contrast to only 2 equal cost path in the conventional DC architecture) meaning that oversubscription of the higher layer links can be significantly mitigated. In Clos-tree topology, as shown in Fig. 1b, links between the core layer
- switches and the aggregation layer switches form a complete bipartite graph [6]. However, ToRs only connect to two aggregation switches as in the conventional tree architecture. The limiting factor for the size of a fat-tree fabric is determined by the number of ports on switches. Fat-tree uniformly uses k-port commodity switches at all layers. All switches at the edge and aggregation lay-
- ers are clustered into k pods, each containing k switches (i.e. k/2 switches at each layer). In other words, edge layer switches have k/2 remaining ports to connect to k/2 hosts. Similarly aggregation layer switches use the remaining k/2ports for connecting $(k/2)^2$ k-port core switches. Eventually, a k-ary fat-tree can support up to $k^3/4$ hosts.
- ¹⁵⁵ Clos/Fat-tree architectures have seen an increasing popularity in modern data centres to achieve high performance and resiliency through their ability to provide better scalability and path diversity than conventional DC topologies [18][19]. However, these architectures require homogeneous switches, and large numbers of links. Upgrading to these architectures in a legacy DC usually
- 160 requires replacing most existing switches and cables. Such radical upgrades are typically prohibitively expensive and time-consuming [20].

2.3. Server-centric Architecture

In server-centric DC architectures, servers are both end-hosts and relaying nodes for multi-hop communications. The most representative fabrics are BCube [21] and DCell [22]. Both BCube and DCell come with custom routing protocols to take advantage of topological properties [23]. As shown in Fig. 1c, in DCell, a server is connected to a number of servers in other cells and to a switch in its own cell. According to [22], a high-level DCell is constructed from low-level DCells (DCell_k, $k \ge 0$) in a recursive manner. DCell₀, as shown in

Fig. 1c, is the building block to construct larger DCells. It has n servers and a mini-switch (n = 4 for DCell₀ Fig. 1c) and all servers in DCell₀ are connected to the mini-switch. And then level-1 DCell₁ is constructed using n + 1 DCell₀s. In DCell₁, each DCell₀ is connected to all the other DCell₀s with one link. And this procedure is repeated to create higher level DCells.

In comparison, a BCube₀ is *n* servers connected to an *n*-port switch. A BCube₁ is comprised of *n* BCube₀'s and *n n*-port switches [21]. In BCube, as illustrated in Fig. 1d, two servers are neighbours if they connect to the same switch. BCube names a server in a BCube_k using an address array $a_k a_{k1} \dots a_0$ $(a_i \in [0, n-1], i \in [0, k])$. Two servers are neighbours if and only if their address arrays differ by a single digit. That is, two neighbouring servers that connect to the same level *i* switch are different at the *i*th digit [21].

A prominent competing advantage of server-centric architecture is the manageability. Since the entire DC fabric is built from servers and a minimal set of network switches, only a single team of engineers is required to maintain and manage the whole architecture. In contrast, multiple (internal and external) professional teams are needed for managing various switches, that are produced by different manufacturers, in switch-centric fabrics. Also, in a server-centric architecture, intelligence can be placed on servers for implementing in-network services such as traffic aggregation, caching as well as deep-packet inspection

etc. However, a server-centric architecture is fundamentally different from traditional network designs and has been seen as an untrusted and complex to update option. In order to promote server-centric architectures, they should offer more significant competing advantages including remarkable reduction in overall deployment cost, improvement in security and resilience. [24].

¹⁹⁵ 2.4. Management Topology

DC network nodes exchange considerable management data in order to configure and maintain the network-wide topology, and consequently, management data intensifies as the topology becomes denser. [25] reports that management traffic can account to approximately 5–10% of the bandwidth during normal operating conditions. With the recent advent of Software Defined Networking (SDN) [26], a paradigm that logically centralises and separates the network control from the data plane, the management network is tightly coupled with the control plane as control decisions must be transmitted between the switches and a central controller. The requirements of a management network are dif-

- ²⁰⁵ ferent from those of the data-carrying network: management traffic is sparse and maintaining high throughput is not critical, however, it is latency-sensitive and failures can be critical to the production network behaviour. Three different types of management networks have been covered in the literature, the simplest is to manage the network *in-band* (IB). In this configuration, both
- ²¹⁰ management and production traffic share the same network. This allows management to be cost-effective but in case of over-utilised production networks, the management network is also hindered. It is possible to mitigate hindrance to management traffic from production traffic through Quality of Service (QoS) enforcement to prioritise management traffic over data traffic [27]. The other
- ²¹⁵ approach is to have a logical or physical Out-of-Band (OOB) network. In a logical OOB network, the core of the network is still shared between management and production traffic, but logical isolation is achieved using VLANs or dedicated OpenFlow forwarding rules [28]. OpenFlow is a communication protocol and API providing access to the forwarding plane of network devices; it is
- ²²⁰ the most widely deployed implementation of the SDN paradigm. In this case, each switch must have a dedicated port for management, increasing the cost as production traffic have less dedicated ports but limiting possible interference

between production and management traffic. However, such setup is still vulnerable to device failure or misconfiguration. Finally, a physical OOB network

can be used in environments where the management network operation is critical, such as a SDN environment without graceful fallback to learning switches or other distributed mechanisms, when the controller is unreachable. In such environments, a different physical network is dedicated to management operations [29][25].

230 3. Server Resource Management

235

The cost of servers in data centres can account up to 45% of running cost per year [4]. It is apparent that achieving high server utilisation is of paramount importance in order to increase Return-on-Investment (RoI). However, server utilisation in DCs can be as low as 10% [30] due to over-provisioning as a result of the desire to provision for peak demand [31].

Achieving high server utilisation is challenging. First, it is difficult for DC operators and customers to plan in advance for "diurnal usage patterns, unpredictable spikes in user and traffic demand, and evolving workloads" [9]. Second, it is very expensive, if not impossible, for both of providers and consumers (who have little control and choice [32]) to configure individual servers so that fine-grained resources, such as, e.g., CPU, memory, storage and network, perfectly match temporal application requirements due to the heterogeneity of servers (i.e., servers have different CPU, RAM and other resource capacities) and the complexity associated with calculating individual resource

- requirements for different services [33]. Third, increasing server utilisation by scheduling multiple services on one physical host can cause severe performance degradation due to resource (e.g. CPU, Memory, Storage and I/O peripheral) contention [34][34][35]. Last, but not least, Cloud DC operators and service providers often need to meet strict QoS guarantees through Service Level Agree-
- ²⁵⁰ ments (SLA). Meeting SLAs is crucial, since it gives confidence to customers to move their ICT infrastructure into the Cloud environments and heavy penalties

are paid by the provider if the SLA is not met. Typically, in order to meet SLA requirements, resources are over-provisioned to meet worst-case demand [36].

Server consolidation is the activity of clustering or reassigning several virtual machines (VMs) running on under-utilised physical servers into fewer hosts, and is used in DCs to improve resource utilisation and reduce operational expenditure (OPEX). VM consolidation has been employed by DC operators to optimise diverse objectives, such as, e.g., server resource (CPU, RAM, net I/O) usage [37][38][39] and energy efficiency [40][41][42], or to meet SLA requirements which are often expressed as CPU or response time guarantees [36][43]. Most server management works take one resource as optimisation objective and treat other resource as constraints or jointly consider multiple resource and SLA constraints. Hence, for the ease of discussion, the research works are broadly categorised based on their main optimisation objectives in the following discussions.

In fact, some production software such as VMware vSphere Distributed Resource Scheduler (DRS) [44], Microsoft System Center Virtual Machine Manager (VMM) [45], and Citrix XenServer [46] offer VM consolidation as one of their major features.

270 3.1. Types of VM consolidation

Server consolidation can be broadly classified as static or dynamic. In static consolidation, or *initial placement*, consolidation algorithms take historical resource utilisation as input to predict future resource use trend based on which VMs are mapped to physical hosts [47][48]. Once initial static consolidation has taken place, VM assignments usually remain unchanged for extended periods of time (e.g., months or even years). It is also done off-line due to the high complexity of consolidation algorithms. Static consolidation is ideal for static workload as it can achieve optimality. On the contrary, dynamic allocation is implemented over short timescales in response to change in resource demand by leveraging the ability to do live migration of VMs.

Dynamic server consolidation is particularly useful for unpredictable workload in which prediction-based mechanisms fail to work. Dynamic consolidation is carried out periodically in shorter timescale that static one to adapt to changes of work demand [39][49][50][40][51][52].

3.2. Server Resource-aware Consolidation Schemes 285

When the users' demand changes, VMs can start competing for physical resources resulting in computation hotspots. Sandpiper [39] is a tool that detects and mitigates hotspots based on physical machine resources such as CPU, network and memory. In order to detect hotspot, Sandpiper implements a monitoring and profiling engine that collects CPU, network and memory usage 290 statistics on VMs and a time-series prediction technique (which relies on the auto-regressive family of predictors) to predict the likelihood of hotspots. The monitoring can be either unobtrusive black-box monitoring which infers CPU, network and memory usage of each VM from external observation (at the host)

- or a more aggressive gray-box monitoring that explicitly puts a daemon inside 295 each VM to monitor/measure resource consumed by individual VMs. For both monitoring approaches, techniques are employed to estimate the peak resource needs. Upon detection of hotspot, it is the migration manager's responsibility to carry out hotspot mitigation. Since optimally deciding which and where
- to migrate is a NP-hard multi-dimensional bin packing problem, the migration manager employs a heuristic to migrate VMs from overloaded servers to underloaded servers where migration overhead (i.e., the amount of data transferred) is minimised. The main drawback of Sandpiper is that it only reactively triggers migration upon detection of hotspot within the infrastructure and does not consider the migration overhead.

310

Entropy [53] achieves optimal VM configuration while also ensures that every VM has access to sufficient memory and allocated CPU share. Entropy has a sensor that periodically probes VMs' CPU usage and working status. Any changes will trigger a reconfiguration process via migration, which consists of virtual machine packing problem (VMPP) and virtual machine re-placement problem (VMRP). Constraint programming is then employed to solve VMPP and VMRP problems. However, in order to reduce migration decision time, when an optimal solution cannot be computed within 1 minute, the computation is aborted and the current best result is used. Entropy takes migration overhead into consideration when making migration decisions, however, it assumes that

the resource demand is known and static over time.

Similar to Sandpiper, ReCon [51] exploits servers' historical resource usage to discover applications that can be consolidated and recommends a dynamic consolidation plan that can be deployed in a multi-cluster data centre. The VM consolidation is formulated as an optimisation problem with multiple con-

straints. The cost function is defined as the running cost of a physical server, predominated by power consumption which is translated into CPU utilisation. Hence, the objective is to minimise the cost given a set of VMs and constraints. However, prediction-based scheme can be sub-optimal when resource require-

ment is dynamic. 325

315

320

In contrast to optimising resources as complete units in aforementioned works, multi-resource schedulable unit (MRSU) [54] breaks CPU, memory, storage and network into small chunks to tackle resource-overallocation problem at fine granularity. MRSU firstly determine schedulable unit in each resource dimension and then compute the number of MRSUs needed for particular in-330 stances. MRSU allocation is a min-max problem and hence a weighted fair heuristic is proposed to solve the problem.

3.3. Energy-aware Consolidation Schemes

VirtualPower [55] is a pioneer work to look into server power management in virtualised environments. When a server is virtualised and shared among 335 guest VMs, its hardware power management cannot function properly due to diverse and inconsistent virtual servers' activities unless all virtual servers agree on the same limitation, e.g. reducing memory bandwidth, concurrently. On the other hand, guest VMs see themselves as independent server and proactively try to manage 'their power states'. Instead of ignoring these built-in power 340

management policies as done by hypervisor, *VirtualPower* exploits the policies as effective hints of individual VM's power state. Therefore, *VirtualPower* can provide a rich set of 'soft' VirtualPower Management (VPM) states to VMs and then use VMs' state changes requests as inputs to manage power locally

on individual physical server and globally (that considers maximum power consumption on all applications in cluster or rack or even the entire data centre level). The VPM states may or may not be actually supported by hardware but are a set of performance states for use by VMs application-specific management policies. The actual power management actions are carried out by the
infrastructure are defined as VPM rules and are realised by VMP mechanisms which include hardware scaling, soft scaling, and consolidation. Different from other related work to manage power at the level of physical hosts, *VirtualPower* enables fine-grained power control at the level of individual VMs. The biggest limitation of VirtualPower is that significant modifications to existing hyper-

While VirtualPower only optimises energy efficiency on individual hosts, pMapper is a controller that places an application onto the most appropriate physical server in order to optimise energy and migration costs, while still meeting some performance guarantees [41]. pMapper employs First Fit Decreasing (FFD) bin-packing algorithm to select an optimal server for any application being migrated in order to minimise power consumption. The algorithm optimises one major resource such as CPU utilisation and treats other resources such as memory and I/O as constraints. pMapper has three main modules: The

infrastructures.

- ³⁶⁵ Monitoring engine monitors all VMs and physical servers and collects their performance (different workloads contribute to the overall CPU and memory utilisation) and power (overall usage) characteristics. The *Performance Manager* examines performance statistics collected from monitoring engine, produces a set of VM sizes that suit current loading and estimate potential benefits should
- ³⁷⁰ any VM resizing is required. The *Power Manager* keeps track of current power consumption and optimises it through CPU throttling. Nevertheless, *pMapper*

employs an *Arbitrator* to ensure consistency between the three modules. Subsequent works [56][33] focused on analysing real data centre application traces, and revealed that there are sufficient variations and correlations amongst applications to be exploited for improving power saving. Hence, *pMapper* has been extended to include some application-awareness features.

In contrast to pMapper, Mistral [42] is a system that emphasises on the optimisation of transient power/performance costs. In Mistral, application performance is reflected in application response time that is modelled as a layered queuing network (LQN). Power consumption of a configuration is based on an

queuing network (LQN). Power consumption of a configuration is based on an empirical non-linear model that concerns CPU utilisation (e.g., power consumption at idle and busy states). Different from pMapper, Mistral takes cost of six transient adaptation actions into account including: changes of a VM's CPU capacity, addition and removal of a VM, live migration of a VM, shutting down and restarting a host, change in response time for the applications and change in power consumption during the adaptation. It use a workload predictor to predict the stability intervals of next adaptation based on historical average resource usage.

3.4. SLA-aware Consolidation Schemes

- A Service Level Agreement (SLA) is a contract that sets the expectations, usually in measurable terms, between the consumer and service provider [57]. In a Cloud computing context, there are infrastructure SLA and service SLA. Infrastructure SLA is established between infrastructure (IaaS) providers and service providers to guarantee sufficient resource and uptime whilst service SLA is established between service providers and their customers and is typically measured in QoS metrics such as application response time: for example, maximum response time of 100 ms with minimal throughput of 100 transactions per second [57][58]. Since a SLA is the cornerstone of how the service provider sets and maintains commitments to the service consumer, optimising resource
- ⁴⁰⁰ utilisation while not violating SLA is also crucially important for operators. Bobroff et al. [36] propose a dynamic resource allocation algorithm for virtu-

alised server environments to maximise the global utilisation of the data centre, while not violating SLAs (i.e., VM's CPU time guarantee) as a result of performance degradation due to overloading. Similar to other VM consolidation

schemes, the algorithm collects and analyses historical usage data on resource utilisation and service quality and predicts the future demand, based on which a sequence migrations are computed. The algorithm (bin packing) is invoked periodically and thus forms a measure-forecast-remap (MFR) optimisation loop. For placement, the algorithm derives a minimum set of servers required to ac-

410 commodate all VMs while not overloading the servers with SLA constraints, i.e. CPU time guarantee. This work, however, shares the similar limitation faced by prediction-based consolidation algorithms in which resource demand and future server resource have to be deterministic.

Breitgand et al. [43] present a Elastic Service Placement Problem (ESPP).

- ⁴¹⁵ Since SLA is defined as meeting the requirements of VM sizing, ESPP aims to optimally allocate variable sized VMs to physical hosts. In ESPP, each service is modelled as an application that spans over a set of VMs. Hence, the ESPP's goal is to maximise the overall profit, which is measured with resulting VM size and probability of VM violation. However, this forms a generalized assignment
- ⁴²⁰ problem (GAP) which is hard to solve. The authors relate ESPP to multiunit combinatorial auctions and hence provide an integer program formulation of ESPP that is amenable to column generation. While column generation is efficient for VM placement in small data centres, it does not scale to large mega data centre.

425 3.5. Network-aware Consolidation Schemes

Meng et al. [48] propose a pioneering work in network-aware initial VM placement. The authors first studied two sets of real traffic traces in operational data centres and observed three key traffic patterns that can be exploited for VM placement: (a) Uneven distribution of traffic volumes from VMs; (b) Stable per-

⁴³⁰ VM traffic at large timescale; and (c) Weak correlation between traffic rate and latency. Hence, VMs can be placed in a way that traffic is localised and managed pairwise. In order to achieve these objectives, they formulated a minimisation problem based on a fixed cost of required bandwidth for each VM, and the cost of communication between the VMs. CPU and memory resources are not used

⁴³⁵ in the algorithm since it is assumed that each VM has the same size and that each server supports a fixed number of VMs. They also showed that the VM placement as an optimisation problem is NP-hard. To reduce the complexity of the proposed algorithm, the authors use a scenario with constant traffic of grouped VMs to simplify the problem space. The VM placement problem is then solved using *min-cut* and *clustering* algorithms to find divisions for VMs.

Wang et al. [50], as an extension with dynamic traffic to [48], propose a VM consolidation scheme to match known bandwidth demands to server's capacity limit. However, in contrast to classical Bin Packing optimisation in which network bandwidth demand is assumed to be static, the authors formulated a NP-hard stochastic bin-packing problem which models the bandwidth demands of VMs as probabilistic distributions and then solve it using an online packing heuristic that assumes each bin has unit capacity. They also assume that network bandwidth is only limited by host network devices rather than topological oversubscription. As only host bandwidth limit is considered, network capacity violations into the DC are possible because aggregation and core layer links are

often oversubscribed.

Ballani et al. [5] tackled the unpredictability of network performance (networkawareness) with novel virtual network abstractions through which tenant virtual networks are mapped to operator's physical networks using an online algo-⁴⁵⁵ rithm. The virtual network abstractions include a virtual cluster representing a topology that is comprised of a number of VMs, a non-oversubscribed virtual switch and a virtual oversubscribed cluster that reflects today's typically oversubscribed two-tier cluster. Once the mapping is done, it is enforced through work (VMs) placement with a fast allocation heuristic - given a set of VMs (with

460 bandwidth requirement) that can be placed in any sub-tree, the algorithm finds the smallest sub-tree that can fit all tenant VMs.

Unlike [48][50][5] which only consider network bandwidth constraint, Shri-

vastava et al. [59] proposed a framework which jointly considers inter-VM dependencies and underlying network topology for VM migration decisions. The

- objective of the optimisation framework is to minimise the overhead (latency, delay, or number of hops) of migration by placing dependent VMs in close proximity in topological location. However, the problem is a variant of multiple knapsack problem and is thus NP-complete. An approximate algorithm, AppAware, is thus proposed in the paper.
- Biran et al. [47] described a minimisation problem to determine the location of VMs in a data centre based on the network bandwidth, CPU, and memory resources. Their formulation is complex and does not scale to the size of data centres, thus they also created two heuristics based on the minimisation algorithm. The calculation is made off-line, and at every change it needs to
- ⁴⁷⁵ be executed. They assume that each user has a specific number of VMs that can only talk to each other, therefore all the VMs are already clustered in their approach.

As computation continues to shift from on-premises IT infrastructure into the Cloud, the computing platform now resides in a warehouse hosting (hundreds of) thousands of physical hosts. Today's Cloud DCs are no longer places that house a large number of co-located servers, rather, they can be seen as a massive warehouse-scale computer [30]. The underpinning DC infrastructures are still a large-scale distributed system and therefore, one should consider converged, DC-wide resource optimisation rather than per-node-based optimisa-

tion. In particular, as data are constantly shuffled across the network, performance is ultimately limited by the network's aggregate capacity as bandwidth is an expensive resource and is highly oversubscribed. It is therefore crucial that any resource management and optimisation scheme takes the network performance into consideration [60] [61][48][50][59][47][13].

⁴⁹⁰ Most of optimisation frameworks either rely on the prediction of future trends based on historical data, and proactively allocate resource based on predicted demand. Some employ directly measured metrics of interest, such as [60] [61], and dynamically adapt to changes according to measurement results.



Figure 2: Granularity of spatial traffic demand measurement in S-CORE [60] has large impact on the performance.

Due to fluctuations in user demands [33][36][6], direct measurement of temporal resource usage seems more appropriate than prediction models in terms of exploiting resource availability in short timescales.

3.6. Open Research Issues

To demonstrate the flexibility of direct measurement, we have developed S-CORE [60][61][62], a distributed communication cost reduction VM migration ⁵⁰⁰ approach which takes network cost into account. As opposed to aforementioned works in network aware server management, S-CORE employs a distributed algorithm based on information available locally through *direct measurement* of bytes exchanged at flow level at each VM to perform migration decisions, rather than using in-network or global statistics. This property allows the algorithm ⁵⁰⁵ to scale and be realistically implementable over large-scale DC infrastructures. It iteratively localises pairwise VM traffic to lower-layer links where bandwidth is not as over-subscribed as it is in the core, and where interconnection switches

is not as over-subscribed as it is in the core, and where interconnection switches are cheaper to upgrade.

Experimental results show that, by directly measuring traffic demand be-⁵¹⁰ tween VMs, S-CORE can achieve significant (up to 87%) communication cost reduction, as shown in Fig. 2. The figure also highlights that S-CORE, when orchestrated with topology awareness (VMs whose traffic load is routed through the highest-layer links of the network topology are prioritised over close-minded VMs), converges significantly faster than when a topology-agnostic round-robin orchestration scheme is used. This demonstrates that the spatial granularity, i.e., the flow level direct traffic measurement, provides useful instantaneous network knowledge that helps improve decision making (reflected in the convergence time).

4. Network Resource Management

For the majority of applications hosted over Cloud environments (e.g., webindexing, distributed data analysis, video processing, scientific computing), data is continuously transmitted over the network to support distributed processing and storage as well as server-to-server communication [63]. These data-intensive or latency-sensitive applications are particularly vulnerable to volatile throughput and packet. Yet, the increased oversubscription ratios from bottom to the

top of prominent multi-root tree network architectures can result in poor serverto-server connectivity hindering application performance [6][16].

Research has demonstrated that supporting protocols have failed to leverage topological advantages of new "scale-out" architectures [64][65]. Most notably, recent measurement work [8][9][66] suggests that current DC networks are largely under-utilised and therefore there is significant room (i.e., up to 20% of network capacity [67]) for operators to improve performance before considering expanding their network infrastructure or upgrading to new fabrics if provisioning is reinforced with a finer-grained control loop. Resource fragmentation can become a performance barrier in DC, resulting in low server utilisation and therefore lower RoI [9][4][16][6].

Fine-grained network resource provisioning requires knowledge of the instantaneous traffic demands, and subsequent harnessing of intelligent resource admission control as well as exploiting the rich path redundancy of the under-

⁵⁴⁰ lying DC network. However, achieving such provisioning using existing legacy mechanisms is faced with two fundamental challenges: First, estimating network load based on historical traffic demands (i.e., predictions) is dubious, since these change rapidly in DC environments and different patterns emerge over diverse

timescales [9]. Second, existing routing protocols such as ECMP fail to support dynamic applications since they are load-agnostic and operate solely on packet 545 header contents [8][15].

4.1. DC Traffic Characteristics

565

Having a better understanding of traffic patterns can help in devising more intelligent traffic management schemes that improve network performance. A number of studies such as [8][9][68][69] have looked into Cloud DC traffic pat-550 terns revealing some unique insights.

In a DC network, ToR Traffic Matrices (TM)s are sparse with significant locality characteristics, since a few ToRs exchange most data with just few other ToRs [68]. Although a significant fraction of traffic appears to be localised inside a rack, congestion does occur in various layers of the infrastructure de-555 spite sufficient capacity being available elsewhere that could be used to alleviate hotspots [8]. Congestion, when it happens, is shown to deteriorate application performance by reducing server-to-server I/O throughput [9]. In terms of flow distribution characteristics, data mining and web service DCs mostly accommo-

- date small (mice) flows typically completed within 1s. Flow inter-arrival times 560 vary from 1 flow per 15 millisecond to 100 flows per millisecond at servers and Top-of-Rack switches, respectively, while on average, there are 10 concurrent flows per server active at any given time [9] [69] [6]. Finally, DC traffic patterns change rapidly and maintain their unpredictability over multiple timescales (as
- opposed to legacy Internet workloads), mainly due to the unpredictable dynamics of external user requests as a result of resource sharing, and the multiplexing of traffic at the level of individual flows, as opposed to large traffic aggregates [6].

Many Cloud applications follow Partition/Aggregate design patterns in which application requests are divided into a number of smaller tasks which are then distributed to a set of workers (servers). The intermediate results yielded from 570 these workers are aggregated to produce a final result. As a result, DCs mainly run host applications with a multi-layer partition/aggregate pattern workflow which exhibits pronounced Partition/Aggregate traffic patterns which exhibit



Figure 3: Traffic engineering is a procedure that optimises network resource utilisation through reshaping of network traffic.

bursty traffic patterns, resulting in Throughput Incast Collapse [70][71][72][73].

575 4.2. DC Traffic Engineering

Traffic engineering (TE) is a technique used by ISPs to select routes that make efficient use of network resources. More specifically TE is a procedure that optimises network resource utilisation through reshaping of network traffic. Fig. 3 illustrates a typical traffic engineering procedure and objectives that are

commonly used. TE consists of a control loop that continuously monitors and evaluates metrics of interest, based on which optimal resource scheduling is computed and deployed. TE techniques can be broadly classified as online and offline, the main distinction between the two being the timescales at which objective values, such as, e.g., link weights and scheduling of traffic flows are adjusted.

Equal Cost Multipath (ECMP): In today's data centres, Equal Cost Multipath (ECMP) is the most commonly used routing to spread traffic flows across redundant shortest paths using hashing on flow tuples (i.e., attributes of packet headers).

590

ECMP is easy to implement as it statically hashes one or more tuples of packet headers and subsequently schedules flows based on their hashed values, ensuring that packets of the same flow are all scheduled over the same path. A commonly used 5-tuple hashing is based on *protocol identifier*, *source/destination network address*, and *source/destination port*.

- **ECMP Challenges:** Recent research has shown that ECMP fails to efficiently leverage path redundancy in DC networks. Studies have demonstrated that network redundancy cannot completely mask all failures, implicitly pointing to the inefficiency of ECMP [66]. Similarly, it is shown that ECMP's static hashing does not take either current network utilisation or flow size into con-
- sideration. Such hashing causes flow collisions that saturates switch buffers and deteriorates overall switch utilisation, resulting in reduction in the network's bandwidth [15]. Moreover, MicroTE [10] has tested ECMP with real DC traffic traces and found that ECMP achieves only 80-85% of optimal performance that can be obtained by solving a linear program with the objective of minimising the
- Maximum Link Utilisation (MLU), assuming full prior knowledge of the traffic matrix every second. The implication of such inefficiency is that, while most of the links in measured DC networks have relatively low utilisation, a small but significant fraction of links appear to be persistently congested [8][9]. As a result, operators will need to upgrade their networks even if they are generally under-utilised.

4.3. Utilisation-aware Traffic Engineering

Hedera [15] is a centralised TE mechanism aiming to resolve ECMP's inability to fully utilise network bandwidth. Hedera's is comprised of three steps. First, large flows (exceeding 10% of the host-NIC bandwidth) detection and scheduling is carried out at the edge switches. Mice flows are still admitted using ECMP. Next, it estimates the natural demand, which is defined as the rate it would grow to in a fully non-blocking network, of large TCP flows. Based on the demand matrix, Hedera uses either global fit or simulated annealing heuristic placement algorithms to find best appropriate paths for different flows.

Eventually, these computed paths are pushed onto the switches. In contrast to only scheduling large flows, VL2 [6] uses Valiant Load Balancing to randomise packet forwarding on a per-flow basis. In VL2, two types of IPs are employed. All switches and interfaces are assigned *location-specific* and applications use *application-specific* IP addresses, which remain unchanged regardless of server

625

locations as a result of VM migrations. Since each server randomly selects a path for each of the flow through the network, it shares intrinsic traffic-agnostic nature of ECMP.

MicroTE [10] is a fine-grained TE approach for DCs that achieves traffic adaptation by exploiting the short-term and partial predictability of the DC traffic demands, to attain overall better link utilisation than ECMP. MicroTE has a centralised controller to gather network demands from the network and maintains a global view of network conditions. A bin-packing heuristic is then employed to find minimum cost path for a given set of (stable) traffic demands. However, unpredictable nature of traffic pattern in production DCs [6] puts MicroTE's usability under question.

The Modified Penalizing Exponential Flow-spliTing (MPEFT) [67] implemented and evaluated an online version of PEFT [74] to provide close to optimal TE for a variety of DC topologies by both shortest and non-shortest paths with exponential penalisation. MPEFT implements a hardware component in a switch to actively gather traffic statistics and link utilisation which are then aggregated to a traffic optimiser. Similar to MicroTE, MPEFT is an online TE that optimises network resource utilisation in short timescales. Different from other schemes, MPEFT does not rely on static predictions of traffic demands which is proven to be unreliable [9]. Rather, MPEFT monitors traffic demands in order to capture temporal traffic variability and then recomputes and schedules traffic to adapt to such variance. However, near optimality is achieved only when per-packet based scheduling is used.

4.4. Energy-aware Traffic Engineering

Cloud DCs are amongst major consumers of electricity and the trend is set for it to rise even higher. It is estimated that amongst each Watt consumed, IT equipment takes about 59% of the share, 33% is attributed to cooling, and 8% is due to power distribution loss [4]. In order to reduce the energy consumed by network equipment, energy-aware routing has been proposed using path diversity to conserve energy. For example, some schemes use as few net-

⁶⁵⁵ work devices as possible to provide the routing service without compromising network performance [75]. Once, the minimum required set of networking nodes has been established, remaining idle ones can be shut-down or put to sleep mode to save energy. However, if the fault-tolerance is not considered, this approach can decrease the resiliency of the network under failure.

ElasticTree [76] is such an optimiser. It continuously monitors the DC's traffic conditions and then determines a set of network elements that must be powered on to meet performance and fault tolerance requirements; Switches or individual ports/links that are not needed can be shutdown. ElasticTree consists of three logical modules: optimiser, routing, and power control. The

- optimiser takes the topology, traffic matrix and a power model as well as the fault tolerance properties (e.g. spare capacity) as inputs to find minimum set of network that meets current traffic conditions. The output of the optimiser is a set of active components to both the power control and the routing modules. The power control is responsible for toggling the power states of switches, ports and line cards. The routing is responsible for flow admission and installs the
- 670

and line cards. The routing is responsible for flow admission and installs the computed routes into the network.

4.5. Latency-aware Traffic Engineering

High-bandwidth Ultra-Low Latency (HULL) [77] is an architecture that is designed for delivering predictable ultra-low latency and high bandwidth utilisation in a DC environment. In order to achieve this goal, HULL uses a combination of three technique: It uses Phantom Queues, which simulate the occupancy of a queue that drains at less than the maximum link rate, adaptive response to ECN marks using DCTCP [71], and packet pacing to smooth out bursts of packet arrivals. From both testbed and simulation experiments, it is reported that HULL mitigates tail latency by a factor of up to 10-40% through trading

off network work throughput [77]. In other words, HULL does not eliminate queuing delay, but prevents it from building up.

Preemptive Distributed Quick (PDQ) [78] flow scheduling is a network protocol designed to improve flow completion time in order to meet deadlines. PDQ borrows some key ideas from legacy real-time scheduling: use Earliest Deadline First to schedule tasks if they need to meet deadlines or use Shortest Job First if flow completion time is of higher priority. PDQ consists of a *PDQ sender* and a *PDQ receiver*. A *PDQ sender* sends a SYN packet to initialise a new flow and a TERM packet to terminate a flow; it is also for retransmitting a packet

⁶⁹⁰ if a timeout occurs. Whereas a *PDQ receiver* extracts the PDQ scheduling header from each data packet to ACK packets. However, since *PDQ* scheduling is a protocol that is fundamentally different from standard protocols existing in production switches, it can only work with custom-made PDQ switches. The PDQ switches share a common flow comparator, which assesses flow criticality
⁶⁹⁵ in order to approximate a range of scheduling disciplines [78]. PDQ requires

switches to perform explicit rate control and flow state maintenance, and hence is complex to implement.

DeTail [69] is a cross-layer scheme for cutting the tail of flow completion faced by DC network traffic flows. At the link layer, DeTail employs flow control to manage port buffer occupancies and create a loss-less fabric. Each switch in the network individually detects congestion by monitoring ingress queue occupancy which is represented with a *drain byte counters*. When it exceeds a predefined threshold, the switch informs the previous hop to pause it transmission by sending a *Pause* message with the specified priorities. Similarly, when

the *drain byte counters* falls below the predefined threshold, the switch resume transmission by sending *Unpause* message to the previous hop. DeTail employs congestion-based load balancing at the network layer by admitting flows on to least congested shortest paths. In comparison to PDQ, DeTail only cuts the tail of flow completion time rather cutting mean completion time.

710

Fastpass [79] is a logically centralised arbiter which allows end hosts to send at line-rate while eliminating congestion at switches. This is achieved by taking packet forwarding decision out of end hosts and carefully schedule all flows in a time-sharing fashion, such that each hosts gets a small fraction of time to use the network exclusively. The centralised arbiter also consists of a path

⁷¹⁵ selection that scatters packets across all available links such that queues will not build up. In comparison with PDQ, and DeTail, Fastpass does not require hardware modification, but needs high precision clock synchronisation and will increase the mean flow completion time due to the communication delay with the controller for every packet in the flow.

Silo [80] provide cloud applications guaranteed network bandwidth, guaranteed packet delay and guaranteed burst allowance in order to ensure predictable network latency for their messages. Silo employs network calculus to map such multi-dimensional network guarantees to queuing constraints on network switches. Compared with other systems, Silo does not requires substantial

changes to hosts or network switches, and hence is readily deployable. However, Silo still relies on the predictability of future demand and make static allocation of bandwidth share.

4.6. Policy-aware Traffic Engineering

- All networks, including data centre networks, are governed by network polir30 cies. Network policy management research to date has either focused on devising new policy-based routing/switching mechanisms or leveraging Software-Defined Networking (SDN) to manage network policies and guarantee their correctness. Joseph et al. [81] proposed *PLayer*, a policy-aware switching layer for DCs consisting of inter-connected policy-aware switches (*pswitches*). Middleboxes are placed off the network path by plugging them into pswitches in PLayer. Based
- on policies specified by administrators, pswitches can explicitly forward different types of traffic through different sequences of middleboxes. PLayer is efficient in enforcing network policies but it does not consider load balancing which is widely used in today's data centres.
- ⁷⁴⁰ Vyas et al. [82] proposed a middlebox architecture, CoMb, to actively consolidate middlebox features and improve middlebox utilization, reducing the number of required middleboxes for operational environments. Policy-Aware Application Cloud Embedding (PACE) [83] is a framework to support application-

wide, in-network policies, and other realistic requirements such as bandwidth

745

and reliability. However, these proposals are not fully designed with VMs migration in consideration, and may put migrated VMs on the risk of policy violation and performance degradation.

Recent developments in SDN enable more flexible middlebox deployments over the network while still ensuring that specific subsets of traffic traverse the desired set of middleboxes [84]. Kazemian et al. [85] presented *NetPlumber*, a real-time policy-checking tool with sub-millisecond average run-time per rule update, and evaluated it on three production networks including Google's SDN, the Stanford backbone and Internet2. Zafar et al. [86] proposed *SIMPLE*, a SDN-based policy enforcement scheme to steer DC traffic in accordance to policy requirements. Similarly, Fayazbakhsh et al. presented FlowTags [87] to leverage SDN's global network visibility and guarantee correctness of policy enforcement.

While these proposals consider policy enforcement as well as traffic dynamism, they require significant network status updates when VM migrations happen.

SYNC [88] and PLAN [89] study the impact of correct policy implementation in the dynamic VM migration environment where change of end-point could imply violation of network policies. Both schemes overcome the difficulty by jointly considering network demand of VMs and policy chaining requirement which demands specific network paths. The problem was modelled as a NPhard stable matching problem. Scalable and fast online heuristic algorithms have been proposed to approximate optimal solution.

4.7. Open Research Issues

Most TE approaches and schemes discussed in this section share a common overall objective: to provide predictable and high-bandwidth network under highly variable traffic demands while also meeting other criteria such as, e.g., energy consumption minimisation. The common underlying control loop includes *monitoring*, *detecting*, and *adapting* promptly to problematic link load, providing a model that reacts to adverse conditions such as congestion.

The transient load imbalance induced by load-agnostic flow admission can

significantly affect other flows using a heavily-utilised link that is common to

⁷⁷⁵ both routes. Flows contending for the bandwidth of the shared link are more likely to create congestion which in turn causes packet drops for flows sharing the same bottleneck link. In most TCP implementations, packet loss will trigger packet retransmission when the retransmission timer expires or when fast-retransmit conditions are met. This additional latency can be a primary contributor to degradation of network performance since the retransmission timeout is a factor of 100 or more than the round trip time over a DC network environment.

Traffic flows are usually shuffled over shortest paths between communicating hosts. In some cases, however, selecting a non-shortest path can be advantageous for avoiding congestion or routing around a faulty path/node [67]. The surveyed

⁷⁸⁵ proposals in this section only use multiple equal cost path in DC environment. In comparison, *Baatdaat* [90] and MPEFT [67] opportunistically include nonshortest paths for packet forwarding. However, finding flow routes in a general network while not exceeding the capacity of any link is the *multi-commodity flow* problem which is NP-complete for integer number of flows. Hence, the routing ⁷⁹⁰ algorithm might consider non-shortest paths constrained by *no more than n* hops longer than the shortest path in practice because it does not significantly increase computation complexity [90].

The performance of current DC networks can be significantly improved if traffic flows can be adequately managed to avoid congestion on bottleneck links. ⁷⁹⁵ This can be achieved by employing more elegant TE to offload traffic from congested links onto spare ones and alleviate the need for topological upgrades. Measurement-based traffic engineering techniques such as *Baatdaat* [90] and MPEFT [67] can play an essential role in response to the immediate load fluctuations. In contrast to reactive traffic engineering such as MicroTE [10], *Baat*-

daat employs a measure-avoid-adapt proactive control scheme based on network programmability. Baatdaat uses direct measurement of link utilisation through dedicated switch-local hardware modules, and constructs a network-wide view of temporal bandwidth utilisation in short timescales through centralised SDN controllers. Subsequently, it schedules flows over both shortest and non-shortest



Figure 4: Granularity of temporal link load measurement (extracted from [90]) has large impact on the performance.

- paths to further exploit path redundancy and spare network capacity in the DC. It is shown in [90] that direct measurement of link utilisation can help make better flow scheduling decisions which result in considerable improvement in maximum link utilisation. We reproduced in Fig. 4 the experimental results under different settings in *Baatdaat*. It can be seen that different measurement (and control) intervals can result in distinctively different performance results - *Baatdaat*'s performance gain over ECMP varies with the measurement timescale, and finer granularity yields better improvement. Even though the improvement is not uniform, in some regions can reach 20% over ECMP, while the practical measurement overhead is very low, especially if a dedicated man-
- ⁸¹⁵ agement topology is used.

5. End-to-End Flow Control and Management

TCP is currently the most widely-used transport protocol carrying about 85% of the traffic on the Internet [91] and over Cloud DCs. Originally, TCP was designed for long-distance, Wide Area Network (WAN) communication with relatively long latencies and low bandwidth, however, DC characteristics are significantly different with Round Trip Times (RTT) below 250μ s, high throughput and a single administrative authority. Under these characteristics, TCP is known to under-utilise network bandwidth, leading in some cases to low through-

put and high latency [92][93]. To improve throughput, large buffers have been

used throughout the network reducing the number of retransmissions, however large buffers cause side effects such as long latencies, traffic synchronisation as well as preventing congestion avoidance algorithms to react promptly to congestion events, leading to buffer-bloat [94]. TCP variants have been proposed to enhance network utilisation over DC environments, however supporting existing
applications, workloads, and keeping the deployment complexity low proves to

be a challenging task.

5.1. Transport Protocols for Data Centre Networks

Most typical DC workloads such as search engines, data mining or distributed file systems, follow the partition-aggregate paradigm where the work is distributed amongst multiple machines and once each machine has computed a partial result, this is aggregated back into a single point [8]. DC traffic generates two types of flows: mice flows that represent 99% of the flows, are small in size (less than a megabyte) and delay-sensitive; and elephant flows of aggregate data carrying most of the bytes over the DC network. These large flows are throughput-sensitive, bound by overall long completion times [71][8].

- While mice flows are created by the query-response mechanism of the partitionaggregate paradigm, elephant flows come from synchronisation mechanisms such as distributed file system replication, database updates, and VM image migration.
- One of the issues is that TCP's conservative nature requires a constant value for the Initial Window (IW) that cannot match the different environment requirements from WAN to DC. If IW is smaller than the congestion window during congestion avoidance phase, new flows will under-utilise the link until enough RTTs have elapsed and the bottleneck capacity has been reached, or
- the flow will terminate before exiting the *slow-start* phase. Over a fast DC network with low latencies, the IW can overshoot the bottleneck capacity, triggering packet loss and unfairness to other flows. Partition-aggregate patterns generate bursts of ON-OFF traffic that can cause packets to be dropped or

delayed [8]. The conservative TCP parameters will wait some time before a packet is retransmitted, however, the time for retransmission can be too long for a packet to meet its deadline.

855

TCP has been shown to have significant issues in DCs mostly because of its congestion avoidance mechanism. The low throughput under bursts of flows and many-to-one communication is referred to as Throughput Incast Collapse [70][92][72]. Due to this issue, Facebook reportedly switched to UDP in order to have tighter control over the congestion mechanisms and avoid the adverse impact of TCP on achievable throughput [71]. Facebook implemented a UDP sliding window mechanism, with a window size inverse proportional to the number of concurrent flows to solve incast collapse when receiving memcache responses, halving the request time [95]. In order to fully utilise the DC network infrastructure, new protocols have been designed to provide better performance, maximise the throughput, minimise latency or reduce queue build-up.

A TCP enhancement, *GIP* [72], has recently been proposed to remedy TCP incast throughput collapse. It has been identified that two types of time-outs (TOs) termed Full window Loss TimeOut (FLoss-TO) and Lack of ACKs (LAck-TO) are the major TOs that cause TCP incast problem. To avoid these TOs, GIP reduces the congestion window at the start of each traffic burst (stripe unit) and retransmits the last packet of every stripe unit for up to three times. However, GIP does not deal with TOs due to packet loss and in high speed environment with small buffers, the extra retransmission of the last packet can needlessly increase buffer occupancy.

Data Center TCP (DCTCP) [71] leverages ECN in modern DCs to provide a multi-bit feedback from a single-bit stream. Instead of treating each ECNmarked packet as a congestion event, it uses the fraction of marked packets to pace the sending rate. In doing so, the presence and extent of congestion can be estimated. The main concept of this approach is to keep the buffer occupancy of each switch as low as possible to prevent new packets from being delayed. DCTCP requires support from the kernel in both the sending and receiving hosts as well as Active Queue Management (AQM) with ECN support in the

- switches. DCTCP has shown to be a significant step forward in preventing throughput collapse, however, it still reacts to an occurring congestion event instead of preventing such congestion to happen. DCTCP has now been included in Windows Server 2012 and Linux 3.18 as an alternative congestion control algorithm.
- 890
- D^3 attempts to treat a DC as a soft real-time system, with each flow having deadline requirements with a revenue loss if it does not. It requires a new protocol that uses explicit rate control to apportion bandwidth according to flow deadlines. To calculate the rate of transmission, D^3 measures the number of flows traversing the interface using flow initiation and termination packets (SYN and FIN) [96]. D^3 , is built on top of DCTCP. However, it has been shown in [97] that D^3 can make unfair bandwidth allocations.

TCP variants have been proposed to avoid queue build-up and therefore prevent high latencies. The Rate Control Protocol (RCP) [98] and the Variable-Structure congestion Control Protocol (VCP) [99] aim to estimate link conges-

- tion and avoid queue build-up, minimise flow completion time while being TCPfriendly. However, both these protocols require end-host and switch support. For long-distance, high-latency environments a significant number of protocols such as STCP, Fast TCP and XCP have been proposed. These protocols have opposite requirements to what is required in a DC. XCP uses a generalisation
- ⁹⁰⁵ of ECN to have explicit feedback instead of using packet drops or the binary mechanism of ECN. Fast TCP estimate the base RTT of the network and uses this value as well as current RTT to estimate the current length of the buffers, the sending rate is adjusted with respect to the number of packets in the queues. These protocols have been optimised to achieve high throughput for long-lived ⁹¹⁰ flows over Long Fat Pipes (LFP).

One recent proposal to tackle latency is TIMELY [100], which reconsiders the applicablity of (round trip time) RTT to estimate queue occupancy. RTT has not been considered in previous proposals because it is prone to noise such as system interrupts and processing in OS stack, given small – tens of microsec-

915 onds – end to end delay in data centre environment. TIMELY overcomes this

limitation by using newly available hardware-assisted NIC timestamps to bypass OS stack. Once measured, TIMELY will compute the delay gradient, which reflects how quickly the queue is building or draining, and use it to compute target sending rate. TIMELY, on the other hand, requires fine-grained and high precision RTT estimation.

920 pr

The issue with TCP is that it is complicated to keep high throughput with low buffer occupancy [71]. Without bloating in-network buffers, the end hosts must be able to pace the delivery of packets to match the characteristics of the link. However, such characteristics are commonly unknown by the end hosts and vary depending on the number of connected hosts and active concurrent flows. In order to establish that a packet has been dropped or lost, some algorithms such as F-RTO can be used but the last resort is to use timeouts. Such timers must be long enough not to worsen congestion by duplicating packets, but also short enough to avoid long delays between transmission and therefore low throughput.

930

925

The current trend in using commodity instead of DC-specific hardware shows that it is unlikely that application-specific hardware will be deployed in such infrastructures, hence algorithms requiring topology or hardware changes are unlikely to be deployed in production environments.

5.2. Open Research Issues

- DC providers have full control over their infrastructure, allowing full network-wide knowledge of the topology, bandwidth, latency and network element properties (e.g., switch buffer sizes). Therefore, the default conservative values used to cope with the unknown characteristics of the Internet can be altered to match the network properties. Recently, with the wide deployment of Software Defined
 Networking (SDN) especially within DC networks [101], the current state of the network can be aggregated at a single or a hierarchy of controllers, and subsequently be used to distribute network knowledge to the end hosts in short timescales [28]. Amazon, Google and Microsoft showed a loss in revenue when response time increased by 100ms, creating a soft real-time constraint on the
- mice flows [102]. Because mice flows are delay-sensitive, it is necessary to pre-

vent the buffer occupancy of the switches to grow too large under traffic bursts as new flows will be delayed significantly. Due to inefficiency of TCP in DC networks, surveyed proposals concentrated on designing an alternative congestion control for TCP. In comparion, Omniscient TCP (OTCP) [103][73] tackles this by exploiting SDN to tune TCP parameters for the operating environment.

With SDN, the TCP parameters can be tuned in real-time with respect to the current network state and prevent buffers from queuing up too much data. If the intra-DC Bandwidth Delay Product (BDP) is known alongside the number of flows on each link, the initial congestion window (IW) can be accurately calculated to match the temporal network properties and increase network-wide 955 throughput. Each flow IW has a fair slice of the network characteristics, and the total number of on-the-fly packets matches the BDP of the network with no buffer occupancy. Tuning IW based on the end-to-end intra-DC BDP, the amount of on-the-fly packets can be reduced to match the link properties and hence reduce buffering. Such approach also prevents undershoot or overshoot 060 of the IW size that can in turn lead to a long *slow-start* phase or packet loss in the first transmission, respectively.

Reducing in-network buffering and shortening *slow-start* will decrease the overall latency and improve the network utilisation. Buffering can be physically reduced by decreasing the size of SRAM in switches, also reducing hard-965 ware cost. However, with shallow buffers, throughput can be significantly lower under bursty traffic due to high number of packet drops and synchronised retransmissions (Incast Collapse). Carefully tuning the Minimum Retransmission Timeout (minRTO) allows high throughput to be achieved while keeping the latency low [92][93].

970

975

950

Omniscient TCP (OTCP) [103][73] uses a SDN controller to keep the global state of the network and tune the minRTO and IW while a new route is being set up. This work shows that the bursty nature of DC traffic combined with large buffers and statically-assigned congestion control parameters, can significantly delay and slow down the transfer of new incoming flows. However, solely

reducing the buffer sizes can prevent high throughput from being achieved if the

default value of minRTO is used. Overall, the measurement-based IW estimation allows for reduced buffer occupancy and consequently bounds the latency; and a smaller minRTO allows throughput to be increased by pushing the congestion control logic back to the end-hosts.

6. Research Challenges and Opportunities

DCs are built on top of legacy hardware and software technologies currently deployed within ISP networks. Cloud operators often assume high similarity between the two environments and hence employ similar resource management principles - *static resource admission* and *over-provisioning* [15]. However, there are fundamental differences that are becoming apparent relatively early in the Cloud DCs' lifetime and will only intensify as their utilisation and commoditisation increase. The main ones relate to the level of aggregation at which resources are provisioned and managed, and at the provisioning timescales. Over the In-

- ⁹⁹⁰ ternet, ISPs operate a relatively limited set of functions on traffic aggregates over long timescales. They can therefore rely on over-provisioning to accommodate short-term fluctuations in load, so long as aggregate demand is predictable over long timescales. On the contrary, Cloud DC operators manage a converged ICT environment where a plethora of diverse resources need to be provisioned
- ⁹⁹⁵ over short timescales, and at a much finer granularity at the level of individual flows, links, virtual machine images, etc. The consequent demand is therefore highly unpredictable over both short and long timescales and DC operators need to respond to rapidly-changing usage patterns, as it has been demonstrated in a number of Cloud DC measurement studies [10][90].
- At the same time, the collocation and central ownership of compute and network resources by a single Cloud service provider offers a unique opportunity for DC infrastructures to be provisioned in an adaptive, load-sensitive and converged manner, so that their usable capacity headroom and return on investment is increased, making Cloud computing infrastructures sustainable in 1005 the long term.

6.1. Network Control Plane Centralisation

Software Defined Networking (SDN) is a paradigm that allows a single control protocol to implement a range of functions such as routing, traffic engineering, access control and Virtual Machine (VM) migration [104][15][40][90].

1010

Network visibility is a unique feature of SDN, inherent to the central controller paradigm. Using such information, globally-informed decisions can be made that would not be possible in a legacy network where the control plane is fully distributed amongst the forwarding elements. A wide range of applications have been developed for SDN, such as, for example, network-wide middlebox and Access Control List (ACL) traversal. A middlebox is usually placed above 1015 the layer it must control, and adding a new one requires changes in the topology. Using SDN, middleboxes can be placed anywhere in the network, and traffic of the machines that must be controlled is redirected using SDN [84, 105, 106]. Such approaches may prevent shortest path routing, yet they allow the network to be much more flexible by programmatically enabling or disabling middleboxes 1020 and requiring no physical change in the topology when new features are added.

A large number of applications have been designed for SDN to demonstrate its benefits for network management and research. A number of studies already discussed in this paper have exploited SDN for resource management over DCs.

For example, Hedera [15] uses OpenFlow to detect large flows in the network, 1025 estimate their demand and compute non-conflicting paths for them. In order to simplify VM migration, VL2 [6] and Portland [107] implemented novel layer 2 addressing and load balancing through OpenFlow.

6.2. Adaptive Data Centre Resource Management

1030

Traditionally, adaptive resource provisioning depends on the reliable prediction of future resource demand in order to estimate future requirements based on historical data sets. Such algorithms first collect a set of sample demands, and then compute a resource allocation (e.g., bandwidth or VM) optimisation. For example, adaptive and Dynamic Multi-path Computation Framework (ADM-

PCF) [108] uses a large set of historical data to analyse and extract features from 1035

traffic flows, which in turn are used to improve resource utilisation and mitigate congestion with guarantee on QoS. A prominent advantage of using this type of schemes is that they can potentially produce remarkable performance gain. It is shown that these algorithms can achieve near-optimal performance because

when the resource requirement is relatively static, the collected set of sample when the resource usages deviate significantly from the anticipated normal behaviour (e.g., flash crowds, newly launched services, etc.), the resulting resource allocation can perform poorly [109][10]. Along with prediction-based provisioning, a more conservative yet costly provisioning approach is to over-provision resources to pre-empt peak demand [110].

6.2.1. Measurement-based Resource Management

There has been an implicit assumption that, similar to ISP networks, Cloud DCs exhibit stable traffic patterns over long timescales and that virtualisation provides performance isolation. However, such assumptions are increas-¹⁰⁵⁰ ingly challenged by measurement studies that demonstrate that performance interference does exist and that user demands change unpredictably causing most virtual machine management models to fail in achieving optimal allocation [34][35][111].

In order to overcome these challenges a more radical approach is required - an approach that directly measures demand and resource utilisation, relaxing the need for unreliable prediction and costly over-provisioning. Measurement of the activity on a target system reveals the utilisation. The utilisation characteristics of the system are then revealed without a specific, previous characterisation of the resource usage being known. Using measurements can remove the need for the complicated, and incomplete models of resource demand [112]. Measurement-based schemes can be used where no model is available. Often, when systems evolve and existing models are no longer suitable to capture their behaviour, measurements allow resource management to adapt to the evolving system.

¹⁰⁶⁵ Measurements of resource utilisation need not be the only input to a man-

agement scheme. Measurement of other parameters such as I/O utilisation, ratio of VM admission, network latency, or the variation in server capacity among heterogeneous servers, are all examples of parameters which would provide important input to adaptive management schemes. After characterising re-

source usage, measurement-based management schemes can dynamically adapt to changes in resource requirements. Such dynamic and adaptive allocation of resources is simply not possible in environments where the imperfect models will result in static resource allocation or when prediction models fail. Measurement-based resource management will adapt resource allocation as usage patterns (and, consequently, resource demands) change. To enable the measurement of different parameters, physical servers, VMs and network nodes need to be appropriately instrumented to independently measure parameters of interest in a distributed manner.

A number of recent studies [60][113][103][67][90][49] have demonstrated that coupling distributed measurement with centralised decision-making is an approach that is able to offer significant improvement in resource provisioning adaptivity. Their results have shown that measurement-based techniques deviate only by a few percent from optimal, operate with less state and information, and offer new, adaptive services.

1085 6.2.2. Open Issues

1090

Measurement is a reactive method used to deal with rapid resource usage fluctuation. In order to capture the rapidly-varying user demand, the measurement intervals need to be small enough to characterise instantaneous change in user demand and resource utilisation [90]. The measurement process also needs to be fine-grained in order to measure resource usage at the same level as resources are leased, e.g., per-VM, per flow, per net-block [113] and then be able to shape admission as necessary.

However, fine-grained temporal and spatial control loops can be expensive because not only more capable and therefore expensive individual hardware is required but also the topology-wide control overhead increases [90][67]. Measurement-based resource shaping may be subject to control loop instability due to the sensitivity of adaptivity. High adaptivity can cause oscillations in resource allocation (e.g., in VM allocation or network routing algorithms) and penalise performance [114][115].

1100

Research efforts are needed to develop robust measurement mechanisms that take correct metrics into account and determine the fine balance between adaptivity and network-wide stability.

6.3. Converged Resource Management for Converged ICT

Virtualisation of server, storage and network resources has enabled the provisioning of converged infrastructures in which these components are virtualised and kept in a pool as a unified resource over DC environments. Resource provisioning for converged infrastructures is managed by a number of control loops at the routing [6][16][22][21][15], transport [116], and virtual machine (VM) [42][39][41] layers. Virtualised servers must be managed carefully to ensure the

maximum utilisation of physical resources. Imperfect VM placement introduces unnecessary cross traffic that will either under-utilise or congest the aggregate and core network links by several factors since VM management algorithms only consider host-local NIC bandwidth constraints. An alternative is to also consider topological constraints such as aggregation links' capacity alongside
conformance to server utilisation limits but this, currently, is still done using static information [49][50][113].

Given the long retransmission timeout and other settings, it is different to manage transient congestion through all TCP variants. However, transient congestion is manageable if it can be detected and if alternate network paths can be exploited in short timescales [69]. For example, DCTCP [71] and HULL [77] can improve overall flow completion time to some extent but they are still unable to overcome the uneven load balancing as a result of static flow hashing due to lack of a global view of the link redundancy in the DC network, and hence still suffer from performance degradation. MPTCP is able to fairly split traffic across multiple TCP subflows but it lacks a mechanism to signal (and guarantee) placement of subflows over physically diverse network paths.

Timely completion of Cloud application workloads heavily depends on the timely completion of network traffic flows. Network congestion is always the main cause of severe network performance degradation. The application layer has an abundance of information that can help the transport and network lay-1130 ers make better decisions. For instance, applications typically know the size of flows and whether they are latency-sensitive or latency-insensitive. By allowing applications to set some flow attributes such as priorities and sizes, more intelligence can be added to the network at different layers to ensure that every flow gets a fair share of the network bandwidth without compromising performance 1135 guarantee.

These examples demonstrate that the underlying DC infrastructure can significantly improve resource usage efficiency and performance through a coordinated, cross-layer approach that vertically spans all networking and systems layers. To this extent, we envisage a converged resource management frame-1140 work for converged infrastructure environments: A unified control loop which will measure, orchestrate and adapt to enable the synergistic and dynamic allocation of network and server resources in order to achieve network-wide performance optimisation and offer predictable services even during short term, high utilisation fluctuations. Such synergy will include adaptive and load-sensitive 1145 server management, topology-aware traffic engineering, and network-informed traffic flow control. This will require the development of devices and mechanisms that will be programmable, will allow the exchange of information between the traditionally isolated layers of the software and network stack and, most importantly, enable timely and measurement-informed service composition within the 1150 network itself.

6.3.1. The Role of DC Networks

DC networks will play a central role in the overall performance of Cloud computing environments since they provide the *central nervous system* for information exchange between cooperating tasks [117]. Moreover, the increased flat-1155

tening of the Internet graph and the penetration of large-scale peering through public Internet exchanges, implies that end-users are only a few AS-hops away from any Cloud service provider and, therefore, the network-internal performance of these converged infrastructures becomes a significant contributor to the end-to-end service time [118].

1160 the

This ubiquitous connectivity outstands the network as the ideal layer for the convergence of the control plane as it can provides a global view of activities from every node to every other node, whether these are servers or switches. Through the DC network, servers and network nodes can interact and disseminate node-local information such as resource provisioning and temporal consumption. By aggregating local knowledge, one can synthesise global performance views taking into consideration diverse metrics, to then apply innovative strategies to optimise the network-wide resource provisioning. Once measurement and control algorithms have computed network-wide objective functions, node-local (re)configuration options (and enforcement) can then be quickly disseminated over the DC network.

6.3.2. The Role of SDN

As measurement and control decisions are carried out by individual servers and network nodes in a distributed manner, SDN can evolve as *the brain* that ¹¹⁷⁵ centrally aggregates statistics and admits resources in a globally optimal (or approximate) manner. This logical centralisation of the control plane, facilitated through SDN, is necessary in order to avoid node-local optima resulting in globally-suboptimal resource admission (e.g., logical bandwidth oversubscription). At the same time, centralising the entirety of control algorithms can be detrimental: not only this would introduce new system vulnerabilities such as single points of failure, in some cases centralised computation of globally-optimal allocation problems is even computationally infeasible [60].

SDN can therefore play an important role in centralising network-wide orchestration and temporal resource information dissemination, yet distribute ¹¹⁸⁵ some of the control plane intelligence throughout the participating physical



Figure 5: Converged resource management requires synergetic optimisation across application, network, transport and physical layers.

network entities that can synergistically analyse real-time workloads and subsequently adapt the network-wide operation gracefully to current load conditions.

Fig. 5 illustrates a framework for converged DC resource management. Each module individually measures node-local resource utilisation. Through the DC
network, these modules communicate events to a SDN controller and receive global decisions back. By integrating node-local intelligence with centralised control, management modules can effectively manage resource admission and shorten the decision-making time.

Nevetheless, realisations of SDN merely offer a match-commit framework
that can be programmable, yet all intelligence is centralised in a limited set of controllers that can easily bottleneck attempts to a converged resource management infrastructure. Recent development in SDN and dataplane programmability might alleviate this problem by allowing the network operators to dynamically reconfigure the dataplane. Using an abstract high level language such as
P4 [119] and a fast network oriented instruction set such as (e)BPF [120] to replace traditional match-action pipeline in switches, custom monitoring and telemetry modules could be available without performance impact on the net-

work. In addition, current SDN protocol specifications do not offer any directives for host participation in a network-wide control plane. Further research is required to identify the fine balance between centralised control and distributed intelligence, cost, as well as in the areas of control theory and combinatorial utility function optimisation to support holistic and adaptive resource management for Cloud Data Centres.

7. Conclusion

- In this paper, we have provided a comprehensive and critical survey of resource management strategies for virtualised Data Centre (DC) infrastructures. We have structured this survey around the fundamental control loops that are typically employed to admit and manage resources, and leverage the infrastructural redundancy to boost performance while minimising operational costs.
- ¹²¹⁵ Diverse DC topologies have been presented that strive to exploit redundant connectivity to maximise the bisection bandwidth between any pair of servers using inexpensive equipment. We have surveyed strategies for Virtual Machine (VM) allocation and management to improve the utilisation and cost efficiency of physical servers, arguably the most costly investment for Cloud DC operators. We
- ¹²²⁰ presented a body of research on resource-aware, energy-aware, network-aware and SLA-aware virtualisation management, and highlighted the fragmented and often conflicting objectives of the different schemes. We have moved onto surveying the management of DC network resources and presented documented evidence on the crucial role of the DC network on application performance. We
- have highlighted the challenges imposed by the distinct characteristics of DC traffic and emerging utilisation patterns, and presented developments on routing and flow scheduling mechanisms to improve utilisation, latency, and energy consumption over DC networks. Furthermore, we have discussed the main developments and implications of transport protocol design over DC networks, how
- ¹²³⁰ congestion control can be adapted for high-speed, low-latency environments, and how multipath transport can be employed to leverage the underlying link redundancy.

Throughout this survey, we have highlighted the challenges imposed on man-

aging Cloud DC infrastructures due to the converged and collocated nature of

- ¹²³⁵ these environments and the consequent co-existence of multiple disjoint control loops, mostly based on legacy mechanisms, each trying to optimise diverse and often contradictory objective functions. We then presented an extensive discussion on research opportunities for adaptive and converged resource management for virtualised DCs. We have highlighted the important role always-
- ¹²⁴⁰ on, measurement-based provisioning can play in this, as well as the potential of Software-Defined Networking (SDN) as an orchestration framework for the converged shaping and allocation of virtualised resources over Data Centre infrastructures.

Acknowledgements

The work has been supported in part by the UK Engineering and Physical Sciences Research Council (EPSRC) grants EP/N033957/1, EP/L026015/1, and EP/L005255/1.

References

1250

 Gartner Inc., Worldwide public cloud services market is forecast to reach \$204 billion in 2016 (2016).

URL http://www.gartner.com/newsroom/id/3188817

- [2] L. Columbus, Gartner predicts infrastructure services will accelerate cloud computing growth (2016). URL http://goo.gl/G58KH3
- [3] R. Miller, http://www.datacenterknowledge.com/archives/2009/05/ 14/whos-got-the-most-web-servers/ (2013).
 - [4] A. Greenberg, J. Hamilton, D. A. Maltz, P. Patel, The cost of a cloud: research problems in data center networks, SIGCOMM Comput. Commun. Rev. 39 (1) (2008) 68–73 (Dec. 2008).

- [5] H. Ballani, P. Costa, T. Karagiannis, A. Rowstron, Towards predictable datacenter networks, ACM SIGCOMM Computer Communication Review 41 (4) (2011) 242–253 (2011).
 - [6] A. Greenberg, J. R. Hamilton, N. Jain, S. Kandula, C. Kim, P. Lahiri, D. A. Maltz, P. Patel, S. Sengupta, VL2: a scalable and flexible data center network, in: Proc. ACM SIGCOMM'09, 2009, pp. 51–62.
 - [7] N. Farrington, A. Andreyev, Facebook's data center network architecture, in: IEEE Optical Interconnects Conf, IEEE, 2013.
 - [8] T. Benson, A. Akella, D. A. Maltz, Network traffic characteristics of data centers in the wild, in: Proceedings of the 10th ACM SIGCOMM conference on Internet measurement, ACM, 2010, pp. 267–280.
 - [9] S. Kandula, S. Sengupta, A. Greenberg, P. Patel, R. Chaiken, The nature of data center traffic: measurements & analysis, in: Proc. ACM SIG-COMM Internet Measurement Conference (IMC'09), 2009, pp. 202–208.
 - [10] T. Benson, A. Anand, A. Akella, M. Zhang, Microte: Fine grained traffic engineering for data centers, in: Proceedings of the Seventh COnference on emerging Networking EXperiments and Technologies, ACM, 2011, p. 8.
 - BCN, Server capacity over-provisioned as cios bring legacy habits to cloud platforms, 2014.
 URL http://goo.gl/cLftcj
- [12] A. Fox, R. Griffith, A. Joseph, R. Katz, A. Konwinski, G. Lee, D. Patterson, A. Rabkin, I. Stoica, Above the clouds: A berkeley view of cloud computing, Dept. Electrical Eng. and Comput. Sciences, University of California, Berkeley, Rep. UCB/EECS 28 (13) (2009).
 - [13] I. Diego, L.-P. Fabio, B. Bar'an, Many-objective virtual machine placement for dynamic environments, in: 2015 IEEE/ACM 8th International Conference on Utility and Cloud Computing (UCC), Limassol, Cyprus, 7-10 December 2015, IEEE, 2015.

1265

- [14] Cisco Systems, Data center: Load balancing data center services solutions reference network design (2004).
- [15] M. Al-Fares, S. Radhakrishnan, B. Raghavan, N. Huang, A. Vahdat, Hedera: Dynamic flow scheduling for data center networks., in: The 7th USENIX Symposium on Networked Systems Design and Implementation (NSDI '10), Vol. 10, 2010, pp. 19–19.
 - [16] M. Al-Fares, A. Loukissas, A. Vahdat, A scalable, commodity data center network architecture, ACM SIGCOMM Computer Communication Review 38 (4) (2008) 63–74 (2008).
 - [17] R. Niranjan Mysore, A. Pamboris, N. Farrington, N. Huang, P. Miri, S. Radhakrishnan, V. Subramanya, A. Vahdat, Portland: a scalable faulttolerant layer 2 data center network fabric, ACM SIGCOMM Computer Communication Review 39 (4) (2009) 39–50 (2009).
 - [18] IBM RedBooks, IBM and Cisco: Together for a World Class Data Center, Vervante, 2013.
 - [19] Cisco, Massively scalable data center at-a-glance (2010). URL http://www.cisco.com/c/dam/en/us/td/docs/solutions/ Enterprise/Data_Center/MSDC/1-0/MSDC_AAG_1.pdf
 - [20] A. R. Curtis, S. Keshav, A. Lopez-Ortiz, Legup: Using heterogeneity to reduce the cost of data center network upgrades, in: Proceedings of the 6th International COnference, Co-NEXT '10, ACM, New York, NY, USA, 2010, pp. 14:1-14:12. doi:10.1145/1921168.1921187.
 URL http://doi.acm.org/10.1145/1921168.1921187
 - [21] C. Guo, G. Lu, D. Li, H. Wu, X. Zhang, Y. Shi, C. Tian, Y. Zhang, S. Lu, BCube: a high performance, server-centric network architecture for modular data centers, in: Proc. ACM SIGCOMM'09, 2009, pp. 63–74.

1300

1310

[22] C. Guo, H. Wu, K. Tan, L. Shi, Y. Zhang, S. Lu, DCell: a scalable and fault-tolerant network structure for data centers, in: Proc. ACM SIG-COMM'08, 2008, pp. 75–86.

1315

- [23] K. Chen, C. Hu, X. Zhang, K. Zheng, Y. Chen, A. V. Vasilakos, Survey on routing in data centers: insights and future directions, Network, IEEE 25 (4) (2011) 6–10 (2011).
- [24] L. Popa, S. Ratnasamy, G. Iannaccone, A. Krishnamurthy, I. Stoica, A cost comparison of datacenter network architectures, in: Proceedings of the 6th International COnference, Co-NEXT '10, ACM, New York, NY, USA, 2010, pp. 16:1–16:12. doi:10.1145/1921168.1921189.
 URL http://doi.acm.org/10.1145/1921168.1921189
- 1325 [25] P. Stalvig, Management networks living outside of production. management networks segregate non-production traffic off production networks., Tech. rep., F5 Networks, Inc. (2008).
 - [26] N. Feamster, J. Rexford, E. Zegura, The road to sdn, Queue 11 (12) (2013)20 (2013).
- ¹³³⁰ [27] Systems, Inc., Cisco safe reference guide, San Jose, USA, 2010.
 - [28] N. McKeown, T. Anderson, H. Balakrishnan, G. Parulkar, L. Peterson, J. Rexford, S. Shenker, J. Turner, Openflow: enabling innovation in campus networks, SIGCOMM Comput. Commun. Rev. 38 (2) (2008) 69–74, doi:10.1145/1355734.1355746 (Mar. 2008). doi:10.1145/1355734.
- 1335 1355746. URL http://doi.acm.org/10.1145/1355734.1355746
 - [29] E. Saitović, I. Ivanović, Network monitoring and management recommendations (2011).
 - [30] U. Hoelzle, L. A. Barroso, The datacenter as a computer: An introduction to the design of warehouse-scale machines, Morgan and Claypool Publishers (2009).

- [31] M. Armbrust, A. Fox, R. Griffith, A. D. Joseph, R. Katz, A. Konwinski,
 G. Lee, D. Patterson, A. Rabkin, I. Stoica, M. Zaharia, A view of cloud computing, Commun. ACM 53 (4) (2010) 50–58, doi:10.1145/1721654.
 1721672 (Apr. 2010). doi:10.1145/1721654.1721672.
 URL http://doi.acm.org/10.1145/1721654.1721672
- [32] S. De Chaves, R. Uriarte, C. Westphall, Toward an architecture for monitoring private clouds, Communications Magazine, IEEE 49 (12) (2011) 130–137, doi:10.1109/MCOM.2011.6094017 (December 2011). doi:10. 1109/MCOM.2011.6094017.
- [33] A. Verma, G. Dasgupta, T. K. Nayak, P. De, R. Kothari, Server workload analysis for power minimization using consolidation, in: Proceedings of the 2009 Conference on USENIX Annual Technical Conference, USENIX'09, USENIX Association, Berkeley, CA, USA, 2009, pp. 28–28.

1360

1345

- URL http://dl.acm.org/citation.cfm?id=1855807.1855835
 - [34] Y. Koh, R. Knauerhase, P. Brett, M. Bowman, Z. Wen, C. Pu, An analysis of performance interference effects in virtual environments, in: Performance Analysis of Systems Software, 2007. ISPASS 2007. IEEE International Symposium on, 2007, pp. 200–209. doi:10.1109/ISPASS.2007. 363750.
 - [35] P. Apparao, R. Iyer, X. Zhang, D. Newell, T. Adelmeyer, Characterization & analysis of a server consolidation benchmark, in: Proceedings of the fourth ACM SIGPLAN/SIGOPS international conference on Virtual execution environments, ACM, 2008, pp. 21–30.
- [36] N. Bobroff, A. Kochut, K. Beaty, Dynamic placement of virtual machines for managing sla violations, in: Integrated Network Management, 2007. IM '07. 10th IFIP/IEEE International Symposium on, 2007, pp. 119–128. doi:10.1109/INM.2007.374776.
 - [37] J. Xu, J. Fortes, Multi-objective virtual machine placement in virtualized

- data center environments, in: IEEE/ACM GreenCom'10, 2010, pp. 179–188. doi:10.1109/GreenCom-CPSCom.2010.137.
 - [38] D. Jayasinghe, C. Pu, T. Eilam, M. Steinder, I. Whally, E. Snible, Improving performance and availability of services hosted on IaaS clouds with structural constraint-aware virtual machine placement, in: IEEE Int. Conf. on Services Computing (SCC'11), 2011, pp. 72–79. doi: 10.1109/SCC.2011.28.
 - [39] T. Wood, P. Shenoy, A. Venkataramani, M. Yousif, Black-box and graybox strategies for virtual machine migration, in: USENIX NSDI'07, 2007.
 - [40] V. Mann, A. Kumar, P. Dutta, S. Kalyanaraman, VMFlow: Leveraging VM mobility to reduce network power costs in data centers, in: Proc. IFIP TC 6 Networking Conf., Vol. 6640 of LNCS, 2011, pp. 198–211.
 - [41] A. Verma, P. Ahuja, A. Neogi, pMapper: power and migration cost aware application placement in virtualized systems, in: Proc. ACM/IFIP/USENIX Int. Conf. on Middleware, 2008, pp. 243–264.
- [42] G. Jung, M. Hiltunen, K. Joshi, R. Schlichting, C. Pu, Mistral: Dynamically managing power, performance, and adaptation cost in cloud infrastructures, in: IEEE Int. Conf. on Distributed Computing Systems (ICDCS'10), 2010, pp. 62–73. doi:10.1109/ICDCS.2010.88.
- [43] D. Breitgand, A. Epstein, SLA-aware placement of multi-virtual ma chine elastic services in compute clouds, in: IFIP/IEEE Int. Symp.
 on Integrated Network Management (IM'11), 2011, pp. 161–168. doi:
 10.1109/INM.2011.5990687.
 - [44] VMWare, http://www.vmware.com/products/vsphere/ features-drs-dpm (2014).
- ¹³⁹⁵ [45] Microsoft, http://technet.microsoft.com/en-us/library/ gg610561.aspx (2014).

1380

- [46] CITRIX, http://www.citrix.com/products/xenserver/overview. html (2014).
- [47] O. Biran, A. Corradi, M. Fanelli, L. Foschini, A. Nus, D. Raz, E. Silvera, A stable network-aware VM placement for cloud systems, Proc. IEEE/ACM Int. Symp. on Cluster, Cloud and Grid Computing (CCGRID '12) (2012) 498–506 (2012).

1405

- [48] X. Meng, V. Pappas, L. Zhang, Improving the scalability of data center networks with traffic-aware virtual machine placement, in: Proc. IEEE INFOCOM'10, 2010, pp. 1–9. doi:10.1109/INFCOM.2010.5461930.
- [49] V. Mann, A. Gupta, P. Dutta, A. Vishnoi, P. Bhattacharya, R. Poddar, A. Iyer, Remedy: Network-aware steady state VM management for data centers, in: Proc. IFIP TC 6 Networking Conf., Vol. 7289 of LNCS, 2012, pp. 190–204.
- [50] M. Wang, X. Meng, L. Zhang, Consolidating virtual machines with dynamic bandwidth demand in data centers, in: Proc. IEEE INFOCOM'11, 2011, pp. 71-75. doi:10.1109/INFCOM.2011.5935254.
 - [51] S. Mehta, A. Neogi, Recon: A tool to recommend dynamic server consolidation in multi-cluster data centers, in: Network Operations and Management Symposium, 2008. NOMS 2008. IEEE, IEEE, 2008, pp. 363–370.
 - [52] M. Chen, H. Zhang, Y.-Y. Su, X. Wang, G. Jiang, K. Yoshihira, Effective vm sizing in virtualized data centers, in: Integrated Network Management (IM), 2011 IFIP/IEEE International Symposium on, 2011, pp. 594–601. doi:10.1109/INM.2011.5990564.
- [53] F. Hermenier, X. Lorca, J.-M. Menaud, G. Muller, J. Lawall, Entropy: A consolidation manager for clusters, in: Proceedings of the 2009 ACM SIGPLAN/SIGOPS International Conference on Virtual Execution Environments, VEE '09, ACM, New York, NY, USA, 2009, pp. 41–50.
 - 51

doi:10.1145/1508293.1508300.

URL http://doi.acm.org/10.1145/1508293.1508300

- [54] D. M. Gutierrez-Estevez, M. Luo, Multi-resource schedulable unit for adaptive application-driven unified resource management in data centers, in: Telecommunication Networks and Applications Conference (ITNAC), 2015 International, IEEE, 2015, pp. 261–268.
- [55] R. Nathuji, K. Schwan, Virtualpower: coordinated power management in virtualized enterprise systems, in: ACM SIGOPS Operating Systems Review, Vol. 41, ACM, 2007, pp. 265–278.
- 1435

1445

1450

- [56] A. Verma, P. Ahuja, A. Neogi, Power-aware dynamic placement of hpc applications, in: Proceedings of the 22Nd Annual International Conference on Supercomputing, ICS '08, ACM, New York, NY, USA, 2008, pp. 175–184. doi:10.1145/1375527.1375555. URL http://doi.acm.org/10.1145/1375527.1375555
- [57] E. Wustenhoff, S. BluePrints, Service level agreement in the data center, Sun Microsystems Professional Series (2002).
- [58] L. M. Vaquero, L. Rodero-Merino, J. Caceres, M. Lindner, A break in the clouds: towards a cloud definition, ACM SIGCOMM Computer Communication Review 39 (1) (2008) 50–55 (2008).
 - [59] V. Shrivastava, P. Zerfos, K.-W. Lee, H. Jamjoom, Y.-H. Liu, S. Banerjee, Application-aware virtual machine migration in data centers, in: INFO-COM, 2011 Proceedings IEEE, 2011, pp. 66–70. doi:10.1109/INFCOM. 2011.5935247.
 - [60] F. P. Tso, K. Oikonomou, E. Kavvadia, D. P. Pezaros, Scalable trafficaware virtual machine management for cloud data centers, in: Distributed Computing Systems (ICDCS), 2014 IEEE 34th International Conference on, IEEE, 2014, pp. 238–247.

- [61] R. Cziva, D. Stapleton, F. P. Tso, D. P. Pezaros, Sdn-based virtual machine management for cloud data centers, in: Cloud Networking (Cloud-Net), 2014 IEEE 3rd International Conference on, IEEE, 2014, pp. 388– 394.
- [62] R. Cziva, S. Jout, D. Stapleton, F. P. Tso, D. P. Pezaros, Sdn-based virtual machine management for cloud data centers, IEEE Transactions on Network and Service Management 13 (2) (2016) 212–225, doi:10.1109/TNSM.2016.2528220 (June 2016). doi:10.1109/TNSM.2016.2528220.
 - [63] G. Wang, T. Ng, The impact of virtualization on network performance of Amazon EC2 data center, in: Proc. IEEE INFOCOM'10, 2010, pp. 1–9.
 - [64] A. R. Curtis, J. C. Mogul, J. Tourrilhes, P. Yalagandula, P. Sharma, S. Banerjee, Devoflow: scaling flow management for high-performance networks, in: ACM SIGCOMM Computer Communication Review, Vol. 41, ACM, 2011, pp. 254–265.
- [65] C. Raiciu, S. Barre, C. Pluntke, A. Greenhalgh, D. Wischik, M. Handley, Improving datacenter performance and robustness with multipath tcp, ACM SIGCOMM Computer Communication Review 41 (4) (2011) 266– 277 (2011).
 - [66] P. Gill, N. Jain, N. Nagappan, Understanding network failures in data centers: measurement, analysis, and implications, in: ACM SIGCOMM Computer Communication Review, Vol. 41, ACM, 2011, pp. 350–361.
 - [67] F. P. Tso, D. P. Pezaros, Improving data center network utilization using near-optimal traffic engineering, IEEE Transactions on Parallel and Distributed Systems 24 (6) (2013) 1139–1148 (2013).
- 1475 [68] S. Kandula, J. Padhye, P. Bahi, Flyways to de-congest data center networks, Proc. ACM HotNets, 2009.

- [69] D. Zats, T. Das, P. Mohan, D. Borthakur, R. Katz, Detail: Reducing the flow completion time tail in datacenter networks, ACM SIGCOMM Computer Communication Review 42 (4) (2012) 139–150 (2012).
- [70] A. Phanishayee, E. Krevat, V. Vasudevan, D. G. Andersen, G. R. Ganger,
 G. A. Gibson, S. Seshan, Measurement and analysis of tcp throughput collapse in cluster-based storage systems., in: FAST, Vol. 8, 2008, pp. 1–14.
 - [71] M. Alizadeh, A. Greenberg, D. A. Maltz, J. Padhye, P. Patel, B. Prabhakar, S. Sengupta, M. Sridharan, Data center tcp (dctcp), ACM SIG-COMM Computer Communication Review 40 (4) (2010) 63–74 (2010).
 - [72] J. Zhang, F. Ren, L. Tang, C. Lin, Taming tcp incast throughput collapse in data center networks, in: Network Protocols (ICNP), 2013 21st IEEE International Conference on, 2013, pp. 1–10. doi:10.1109/ICNP.2013.
 6733609.
 - [73] S. Jouet, C. Perkins, D. Pezaros, Otcp: Sdn-managed congestion control for data centre networks, in: IEEE/IFIP Network Operations and Management Symposium (NOMS), 2016. URL http://eprints.gla.ac.uk/114177/
- [74] D. Xu, M. Chiang, J. Rexford, Link-state routing with hop-by-hop forwarding can achieve optimal traffic engineering, in: Proc. IEEE INFO-COM'08, 2008, pp. 466–474.
 - [75] Y. Shang, D. Li, M. Xu, Energy-aware routing in data center network, in: Proceedings of the first ACM SIGCOMM workshop on Green networking, ACM, 2010, pp. 1–8.
- 1500
- [76] B. Heller, S. Seetharaman, P. Mahadevan, Y. Yiakoumis, P. Sharma, S. Banerjee, N. McKeown, Elastictree: Saving energy in data center networks., in: NSDI, Vol. 3, 2010, pp. 19–21.

[77] M. Alizadeh, A. Kabbani, T. Edsall, B. Prabhakar, A. Vahdat, M. Yasuda,

1505

1515

Less is more: Trading a little bandwidth for ultra-low latency in the data center, in: Proc. of NSDI, 2012.

[78] C.-Y. Hong, M. Caesar, P. Godfrey, Finishing flows quickly with preemptive scheduling, ACM SIGCOMM Computer Communication Review 42 (4) (2012) 127–138 (2012).

[79] J. Perry, A. Ousterhout, H. Balakrishnan, D. Shah, H. Fugal, Fastpass: A centralized zero-queue datacenter network, in: Proceedings of the 2014 ACM conference on SIGCOMM, ACM, 2014, pp. 307–318.

[80] K. Jang, J. Sherry, H. Ballani, T. Moncaster, Silo: Predictable message latency in the cloud, in: Proceedings of the 2015 ACM Conference on Special Interest Group on Data Communication, ACM, 2015, pp. 435– 448.

- [81] D. A. Joseph, A. Tavakoli, I. Stoica, A policy-aware switching layer for data centers, in: ACM SIGCOMM Computer Communication Review, Vol. 38, ACM, 2008, pp. 51–62.
- [82] V. Sekar, N. Egi, S. Ratnasamy, M. K. Reiter, G. Shi, Design and implementation of a consolidated middlebox architecture., in: NSDI, 2012, pp. 323–336.
 - [83] L. E. Li, V. Liaghat, H. Zhao, M. Hajiaghayi, D. Li, G. Wilfong, Y. R. Yang, C. Guo, PACE: Policy-aware application cloud embedding, in: Proceedings of 32nd IEEE INFOCOM, 2013.
 - [84] A. Gember, P. Prabhu, Z. Ghadiyali, A. Akella, Toward software-defined middlebox networking, in: Proceedings of the 11th ACM Workshop on Hot Topics in Networks, ACM, 2012, pp. 7–12.
 - [85] P. Kazemian, M. Chang, H. Zeng, G. Varghese, N. McKeown, S. Whyte, Real time network policy checking using header space analysis, in:

1530

USENIX Symposium on Networked Systems Design and Implementation (NSDI), 2013.

[86] Z. A. Qazi, C.-C. Tu, L. Chiang, R. Miao, V. Sekar, M. Yu, Simplefying middlebox policy enforcement using sdn, ACM SIGCOMM Computer Communication Review 43 (4) (2013) 27–38 (2013).

1535

1540

1550

1555

- [87] S. K. Fayazbakhsh, L. Chiang, V. Sekar, M. Yu, J. C. Mogul, Enforcing network-wide policies in the presence of dynamic middlebox actions using flowtags, in: Proc. USENIX NSDI, 2014.
- [88] L. Cui, R. Cziva, F. P. Tso, D. Pezaros, Synergistic policy and virtual machine consolidation in cloud data centers (2016). URL http://eprints.gla.ac.uk/112944/
 - [89] L. Cui, F. P. Tso, D. P. Pezaros, W. Jia, Plan: A policy-aware vm management scheme for cloud data centres (December 2015). URL http://eprints.gla.ac.uk/112857/
- [90] F. Tso, G. Hamilton, R. Weber, C. Perkins, D. Pezaros, Longer is better: exploiting path diversity in data center networks, in: IEEE International Conference on Distributed Computing Systems (ICDCS), 2013, pp. 430– 439.
 - [91] D. Murray, T. Koziniec, The state of enterprise network traffic in 2012, in: Communications (APCC), 2012 18th Asia-Pacific Conference on, IEEE, 2012, pp. 179–184.
 - [92] Y. Chen, R. Griffith, J. Liu, R. H. Katz, A. D. Joseph, Understanding tcp incast throughput collapse in datacenter networks, in: Proceedings of the 1st ACM workshop on Research on enterprise networking, WREN '09, ACM, New York, NY, USA, 2009, pp. 73–82. doi:10.1145/1592681. 1592693.

URL http://doi.acm.org/10.1145/1592681.1592693

- [93] V. Vasudevan, A. Phanishayee, H. Shah, E. Krevat, D. G. Andersen, G. R. Ganger, G. A. Gibson, B. Mueller, Safe and effective fine-grained tcp retransmissions for datacenter communication, in: Proceedings of ACM SIGCOMM, Barcelona, Spain, 2009.
- [94] J. Gettys, K. Nichols, Bufferbloat: Dark buffers in the internet, Queue
 9 (11) (2011) 40:40-40:54, doi:10.1145/2063166.2071893 (Nov. 2011).
 doi:10.1145/2063166.2071893.
- ¹⁵⁶⁵ URL http://doi.acm.org/10.1145/2063166.2071893
 - [95] R. Jeff, High performances at massive scale (2009). URL http://video-jsoe.ucsd.edu/asx/JeffRothschildFacebook. asx
 - [96] C. Wilson, H. Ballani, T. Karagiannis, A. Rowtron, Better never than late: Meeting deadlines in datacenter networks, in: ACM SIGCOMM Computer Communication Review, Vol. 41, ACM, 2011, pp. 50–61.
 - [97] B. Vamanan, J. Hasan, T. Vijaykumar, Deadline-aware datacenter tcp (d2tcp), SIGCOMM Comput. Commun. Rev. 42 (4) (2012) 115–126, doi:10.1145/2377677.2377709 (Aug. 2012). doi:10.1145/2377677. 2377709.

URL http://doi.acm.org/10.1145/2377677.2377709

- [98] N. Dukkipati, Rate control protocol (rcp): Congestion control to make flows complete quickly, Ph.D. thesis, Stanford, CA, USA, aAI3292347 (2008).
- [99] Y. Xia, L. Subramanian, I. Stoica, S. Kalyanaraman, One more bit is enough, IEEE/ACM Trans. Netw. 16 (6) (2008) 1281–1294, doi:10.1109/ TNET.2007.912037 (Dec. 2008). doi:10.1109/TNET.2007.912037. URL http://dx.doi.org/10.1109/TNET.2007.912037
- [100] R. Mittal, N. Dukkipati, E. Blem, H. Wassel, M. Ghobadi, A. Vahdat,
 Y. Wang, D. Wetherall, D. Zats, et al., Timely: Rtt-based congestion

1560

1570

control for the datacenter, in: Proceedings of the 2015 ACM Conference on Special Interest Group on Data Communication, ACM, 2015, pp. 537– 550.

- [101] S. Jain, A. Kumar, S. Mandal, J. Ong, L. Poutievski, A. Singh, S. Venkata,
 J. Wanderer, J. Zhou, M. Zhu, J. Zolla, U. Hölzle, S. Stuart, A. Vahdat, B4: Experience with a globally-deployed software defined wan, in: Proceedings of the ACM SIGCOMM 2013 Conference on SIGCOMM,
 SIGCOMM '13, ACM, New York, NY, USA, 2013, pp. 3–14. doi: 10.1145/2486001.2486019.
- ¹⁵⁹⁵ URL http://doi.acm.org/10.1145/2486001.2486019
 - [102] E. Schurman, J. Brutlag, The user and business impact of server delays, additional bytes, and http chunking in web search (2009).
 URL http://velocityconf.com/velocity2009/public/schedule/ detail/8523
- 1600 [103] S. Jouet, D. Pezaros, Measurement-based tcp parameter tuning in cloud data centers, IEEE ICNP, 2013.
 - [104] A. Tavakoli, M. Casado, T. Koponen, S. Shenker, Applying nox to the datacenter., in: HotNets, ACM, 2009.
- [105] R. Cziva, S. Jouet, D. Pezaros, Gnfc: Towards network function cloudifi cation (November 2015).
 URL http://eprints.gla.ac.uk/105962/
 - [106] R. Cziva, S. Jouet, K. White, D. Pezaros, Container-based network function virtualization for software-defined networks (2015).
 URL http://eprints.gla.ac.uk/105926/
- ¹⁶¹⁰ [107] R. Niranjan Mysore, A. Pamboris, N. Farrington, N. Huang, P. Miri, S. Radhakrishnan, V. Subramanya, A. Vahdat, Portland: a scalable faulttolerant layer 2 data center network fabric, ACM SIGCOMM Computer Communication Review 39 (4) (2009) 39–50 (2009).

[108] M. Luo, Y. Zeng, J. Li, W. Chou, An adaptive multi-path computation framework for centrally controlled networks, Computer Networks 83 (2015) 30-44 (2015).

1615

1630

1640

- [109] H. Wang, H. Xie, L. Qiu, Y. R. Yang, Y. Zhang, A. Greenberg, Cope: traffic engineering in dynamic networks, ACM SIGCOMM Computer Communication Review 36 (4) (2006) 99–110 (2006).
- [110] R. Moreno-Vozmediano, R. S. Montero, I. M. Llorente, Elastic management of cluster-based services in the cloud, in: Proceedings of the 1st workshop on Automated control for datacenters and clouds, ACM, 2009, pp. 19–24.
- [111] W. Voorsluys, J. Broberg, S. Venugopal, R. Buyya, Cost of virtual ma chine live migration in clouds: A performance evaluation, in: Cloud Com puting, Springer, 2009, pp. 254–265.
 - [112] V. Lopez, H. Hamann, Measurement-based modeling for data centers, in: Thermal and Thermomechanical Phenomena in Electronic Systems (ITherm), 2010 12th IEEE Intersociety Conference on, 2010, pp. 1–8. doi:10.1109/ITHERM.2010.5501415.
 - [113] F. Tso, G. Hamilton, K. Oikonomou, D. Pezaros, Implementing scalable, network-aware virtual machine migration for cloud data centers, in: IEEE International Conference on Cloud Computing (IEEE CLOUD), 2013, pp. 557–564.
- URL http://eprints.gla.ac.uk/83096/
 - [114] R. Gao, C. Dovrolis, E. W. Zegura, Avoiding oscillations due to intelligent route control systems., in: INFOCOM, 2006.
 - [115] S. Akhshabi, A. C. Begen, C. Dovrolis, An experimental evaluation of rateadaptation algorithms in adaptive streaming over http, in: Proceedings of the Second Annual ACM Conference on Multimedia Systems, MMSys '11,

ACM, New York, NY, USA, 2011, pp. 157–168. doi:10.1145/1943552.

1943574.

URL http://doi.acm.org/10.1145/1943552.1943574

- [116] C. Raiciu, S. Barre, C. Pluntke, A. Greenhalgh, D. Wischik, M. Handley, Improving datacenter performance and robustness with multipath TCP, in: Proc. ACM SIGCOMM'11, 2011, pp. 266–277.
 - [117] D. Abts, B. Felderman, A guided tour through data-center networking, Queue 10 (5) (2012) 10 (2012).
- [118] B. Ager, N. Chatzis, A. Feldmann, N. Sarrar, S. Uhlig, W. Willinger,

1650

1645

- Anatomy of a large european ixp, in: Proceedings of the ACM SIGCOMM 2012 conference on Applications, technologies, architectures, and protocols for computer communication, ACM, 2012, pp. 163–174.
- [119] P. Bosshart, D. Daly, G. Gibb, M. Izzard, N. McKeown, J. Rexford, C. Schlesinger, D. Talayco, A. Vahdat, G. Varghese, D. Walker, P4: Pro-
- 1655
- gramming protocol-independent packet processors, SIGCOMM Comput. Commun. Rev. 44 (3) (2014) 87–95, doi:10.1145/2656877.2656890 (Jul. 2014). doi:10.1145/2656877.2656890. URL http://doi.acm.org/10.1145/2656877.2656890
- [120] S. Jouet, R. Cziva, P. Dimitrios P., Arbitrary packet matching in openflow,in: HPSR 2015, 2015.



Fung Po Tso received his BEng, MPhil and PhD degrees from City University of Hong Kong in 2006, 2007 and 2011 respectively. He is currently lecturer in the Department of Computer Science at the Liverpool John Moores University (LJMU). Prior to joining LJMU, he worked as SICSA Next Generation Internet Fellow at the School of Computing Science, University of Glasgow. He

has published more than 20 research articles in top venues and outlets. His research interests include: network measurement and optimisation, cloud data centre resource management, data centre networking, software defined networking (SDN), virtualisation, distributed systems as well as mobile computing and

system.



Simon Jouet received a M.Eng in Electronic and Software Engineering from the University of Glasgow in 2012. He is currently a Research Assistant at the School of Computing Science, University of Glasgow. His research focuses on the cross-layer benefits of centralized control in Cloud Data Centre in order to optimize resource utilisation, network and compute performance as well as energy

efficiency. Current research focuses on the centralisation of network state, topology, routing and forwarding through Software Defined Networking (SDN) and orchestration through Network Function Virtualization (NFV).



Dimitrios P. Pezaros received the B.Sc. (2000) and Ph.D. (2005) degrees in Computer Science from the University of Lancaster, UK. He is currently Senior Lecturer (Associate Professor) and director of the Networked Systems Research Laboratory (netlab) at the School of Computing Science, University of Glasgow, which he joined in 2009. His research is focusing on the resilient and effi-

1665

cient operation of future virtualised networked infrastructures through the exploitation of converged network-server resource management mechanisms, Software-Defined Networking (SDN), and Network Function Virtualisation (NFV). He has received significant funding for his research in the above areas from the UK Engineering and Physical Sciences Research Council (EPSRC), the University of Glasgow, the London Mathematical Society (LMS),

and the industry.

Previously, he has worked as a postdoctoral and senior research associate on a number of EPSRC and EU-funded projects in the areas of performance measurement and evaluation, network management, cross-layer optimisation, QoS

1700

analysis and modelling, and network resilience. Dimitrios has been a doctoral fellow of Agilent Technologies (2000-2004). He is a Chartered Engineer, and a Senior Member of the IEEE.